

TT16-MW07

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY

Log No. 104622  
Permit No.  
Basin 101

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 54763

1. OWNER DEPT OF NAVY NAS FALLON ADDRESS AT WELL LOCATION 4755 Pastore Rd  
MAILING ADDRESS 4755 Pastore Rd Fallon, NV. 89496  
Subdivision Name: NAS, FALLON County: Churchill

2. LOCATION SW 1/4 SE 1/4 Sec 23 T 18 N R 29 E Latitude UTM E 1150352854 NAD 27  
PERMIT/WAIVER No. IRP Longitude N 4362870 NAD 83/WGS 84  
Issued by Water Resources Parcel No. 006-611-01

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other  
4. PROPOSED USE  
 Domestic  Irrigation  Test  Cable  Rotary  RVC  
 Municipal/Industrial  Monitor  Stock  Air  Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
SILTY SAND		0'	5'	5'
CLAY	Δ	5'	7'	2'
SILT		7'	9'	2'
SAND		9'	18'	9'
Δ → groundwater encountered at 10'				

9. WELL CONSTRUCTION  
Depth Drilled 18' Feet Depth Cased 18' Feet  
HOLE DIAMETER (BIT SIZE)  
8" From 0' To 18' Feet  
Inches Feet Feet Feet  
Inches Feet Feet Feet  
Inches Feet Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		SCH. 40	0'	18'

Perforations:  
Type of perforation Manufactured Slotted  
Size of perforation .010  
From 18' feet to 3' feet  
From feet to feet  
From feet to feet  
From feet to feet  
From feet to feet

Annular Seal:  Yes  No  
 Neat Cement 0' to 1'  Pumped  Paired  
 Cement Grout to  Pumped  Paired  
 Concrete Grout to  Pumped  Paired  
 ≥30% Bentonite Grout to  Pumped  Paired  
Gravel Pack:  Yes  No 18' to 2 1/2'  Pumped  Paired  
Type: 2 1/2" sand  
Bentonite Chips:  Yes  No 2 1/2' to 1'  Pumped  Paired  
Type: 3/8" Panbrik chips

Date started: 10.13.07, 20 07  
Date completed: 10.13.07, 20 07

7. Water Level  
Static water level: 6' feet below land surface  
Artesian Flow: G.P.M. P.S.I.  
Water Temperature: °F  
Quality:

8. WELL TEST DATA

TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Gregg Drilling Contractor  
Address 950 Howe Rd Contractor  
Martinez, CA 94553  
Nevada contractor's license number C23-0038113  
issued by the State Contractor's Board  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2328  
Signed [Signature] Driller performing actual drilling on site or contractor  
Date 10.13.07