



STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY  
Log No. 1099413  
Permit No. \_\_\_\_\_  
Basin 031

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 60853

1. OWNER Eldon Crawford ADDRESS AT WELL LOCATION 25 Mi. W/2 Mi N on Jungo  
MAILING ADDRESS 5195 Kirkway Drive Winnemucca NV Winnemucca, NV 89445

Subdivision Name: \_\_\_\_\_ County: humboldt

2. LOCATION NE 1/4 SW 1/4 Sec 21 T 36 N/S R 34 E Latitude N40°977.25 UTM E  NAD 27  
PERMIT/WAIVER NO. 38308 Longitude W118°17302 N  NAD 83/WGS 84  
Issued by Water Resources Parcel No. \_\_\_\_\_

3. TYPE OF WELL  Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled?  Yes  No  
If yes, what is replacement well NOI? \_\_\_\_\_  
Is there an existing well log?  Yes  No  
If yes, what is NDWR well log #? \_\_\_\_\_

4. EXISTING WELL CONSTRUCTION  
Depth Drilled 310 Feet Depth Cased 310 Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		.250	+1	65

Existing Perforations:  
Type of perforation \_\_\_\_\_  
Size of perforation \_\_\_\_\_  
From 110 feet to 310 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

5. WATER LEVEL  
Static water level: 110 feet below land surface  
Artesian flow: no G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: cool °F Quality good

6. Additional Notes or Comments  
**Camera well perf from 102' to 310'. Perf with hydraulic punch from 60' to 310' with 4 holes per foot. Pump HydroGrout 30 from TD to 96'. Let set. Pour Native material from 96' to 50'. Pour 3/4 chips from 20' to 50' mix and install cement.**

N 40.977365  
W 118.172036 NAD27

7. WELL PLUGGING PROCEDURE

Was well cleaned out to total depth?  Yes  No  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

Was the well contaminated?  Yes  No  
Was the casing pulled?  Yes  No  
Was the casing over drilled?  Yes  No

If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used: Hydraulic Punch  
From 50 feet to 310 feet Number of perfs per linear foot 4  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_

8. WELL PLUGGING MATERIALS

Material Used			
Hydrogrout			
From <u>310</u> feet to <u>60</u> feet	<u>ut</u>	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From _____ feet to _____ feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From _____ feet to _____ feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From _____ feet to _____ feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From _____ feet to _____ feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From _____ feet to _____ feet		<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured

Neat Cement Fluid Weight \_\_\_\_\_ lbs/gal  
Bentonite Grout 30 % bentonite

Date Started 01/02/08  
Date Completed 01/02/08

9. DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Fred Anderson Drilling, Inc.

Address 10760 S. Grass Valley Rd

Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 021467

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1375

Signed Fred Anderson Drilling, Inc.  
By driller performing actual drilling on site or contractor

Date January 10, 2008