



STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please fill in this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY

Log No. 105060
 Permit No. _____
 Basin 153

NOTICE OF INTENT NO. 59210

1. OWNER Diamond Valley Ranch
 MAILING ADDRESS P.o. Box 920 Lake Oswego, OR 970
 Lake Oswego, OR 97034

ADDRESS AT WELL LOCATION Diamond Valley #4
 Eureka, NV 89316

2. LOCATION NE 1/4 NE 1/4 Sec 28 T 21 R 53
 PERMIT NO 19542 Parcel No.

Latitude 39.66151 Longitude -116.00677 WGS 84
 Subdivision Name _____ County Eureka

3. TYPE OF WELL
 Irrigation

Is this well being plugged because a replacement well was drilled?
 If yes what is replacement well NOI?

Yes
~~40205~~

Is there an existing well log? Yes
 If yes, what is NDWR well log #? 7953

4. EXISTING WELL CONSTRUCTION
 Depth Drilled 210 Feet Depth Cased 210 Feet

EXISTING CASING SCHEDULE

| Size O.D. (inches) | Weight/Ft. (Pounds) | Wall Thickness | From (Feet) | To (Feet) |
|--------------------|---------------------|----------------|-------------|-----------|
| 16 | 42. | 0.250 | 0 | 210 |

Existing Perforations:

Type perforation Johnson Free-Flo
 Size perforation 0.250
 From 190 feet to 210 feet
 From 120 feet to 140 feet

7. WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? Yes
 If well was not cleaned out to total depth, please explain why:

Was well contaminated? No
 Was casing pulled? No
 Was casing overdrilled? No

If casing was left in place, please show where additional perforations were made:

Additional Perforations:

Type perforator used: Air Roller
 From 0 To 120 Number of perfs per linear foot 16
 From 140 To 190 Number of perfs per linear foot 16

5. WATER LEVEL

Static Water Level 129 feet below land surface
 Artesian Flow G.P.M. P.S.I.
 Water temperature ° F Quality

8. WELL PLUGGING MATERIALS

Material
 From 0 Feet to 50 Feet Neat Cement Pumped
 From 50 Feet to 210 Feet Bentonite Pumped

6. Additional Notes or Comments

Pumped in 106 bags of 20% Bentonite grout from bottom to 50 ft.
 Installed 3 yds of neat cement from 50 ft. to surface.

N 39.661590
 W 116.005769 NAD27

Neat Cement Fluid Weight 156 lbs/gal
 Bentonite Grout 20 % Bentonite
 Date Started 3/14/2007
 Date Completed 11/6/2007

9. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Parsons Drilling, Inc.
 Contracto
 Address 403 McLean Road
 Fallon, NV 89407

Contracto
 Nevada contractor's license number 29064
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 1753
 Division of Water Resource, the on-site driller

Signed Wayne Parson
 By driller performing the actual drilling on site or contract
 Date 12/5/2007

2006 JAN -2 AM 11:46

2006 JAN -2 AM 11:46

2006 JAN -2 AM 11:46