STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 105127
Permit No.
Basin 066

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61270

1. OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 388
Valmy, NV 89435

ADDRESS AT WELL LOCATION Twin Creeks Mine
Hole #TMO-30047
Subdivision Name: County: Humboldt

2. LOCATION SE ¼ SE ¼ Sec 30 T 39N N/S R 43 E
PERMIT/WAIVER No. M/O-1479
Issued by Water Resources Parcel No.

Latitude 41.227923
Longitude 117.164170
UTM E 486240.34215 [x] NAD 27
N 4563859.86554 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [x] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[x] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	775	775
Bedrock		775	830	55
830				
Abandon hole ~~820~~' to 800'				
neat cement 168 gallons				

Date started: 3-Dec , 20 07
Date completed: 17-Dec , 20 07

7. *Water Level*
Static water level: 356 feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: 72 °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [x] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
680	25	N/A	5 hours

9. *WELL CONSTRUCTION*
Depth Drilled 830 Feet Depth Cased 800 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
11 1/2	Inches	0	Feet	20	Feet
8 1/2	Inches	20	Feet	830	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5		.25	0	800

Perforations:
Type of perforation Slotted
Size of perforation 0.125
From 360 feet to 800 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [x] Yes [ ] No
[x] Neat Cement 0 to 51 [x] Pumped [ ] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [x] Yes [ ] No 359 to 800 [ ] Pumped [x] Poured
Type: SRI 1/4" + or -
Bentonite Chips: [x] Yes [ ] No 359 to 51 [ ] Pumped [x] Poured
Type: 3/8" bentonite chip

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1777
Signed Dennis L. White (By driller performing actual drilling on site or contractor)
Date 12/17/2007

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY