STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 105219
Permit No.
Basin 061

NOTICE OF INTENT NO. 61273

1 OWNER Barrick Gtold Strike Mines
MAILING ADDRESS PO Box 29
NE Elko, NV 89803

ADDRESS AT WELL LOCATION North Area
Hole #NA3A
Subdivision Name: *County:* Eureka

2 LOCATION ¼ SW ¼ Sec 33 T 36N N/S R 50 E
PERMIT/WAIVER No order # 1038
Issued by Water Resources *Parcel No.*

Latitude 40.954351 Longitude 116.329757
UTM E 4533694 N 0556409
[x] NAD 27 [ ] NAD 83/WGS 84

3 TYPE OF WELL
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [x] Monitor [ ] Stock

Is this well being plugged because a replacement well was drilled? Yes
If yes, what is replacement well NOI? 61274

Is there an existing well log? Yes
If yes, what is NDWR well log #? 72353

4 *EXISTING WELL CONSTRUCTION*
Depth Drilled 820 Feet Depth Cased 800 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
13.375	68.75	.500	0	22
2	5.02	.218	+2	780
1.25	3.00	.191	+2	360

Existing Perforations:
Type of perforation Slotted
Size of perforation 0.125

From	2" 800	feet to	780	feet	
From	1.25 380	feet to	360	feet	
From		feet to		feet	
From		feet to		feet	
From		feet to		feet	

5 2" = 152 *WATER LEVEL*
Static water level 1.25 = 179 feet below land surface
Artesian flow No G.P.M. N/A P.S.I
Water temperature °F Quality

6 Additional Notes or Comments
2" well filled with cement from total depth to surface
1 1/4" well filled with neat cement from total depth to surface

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [ ] yes [x] no
If well was not cleaned out to total depth, please explain why: It was a clean hole

Was the well contaminated? [ ] yes [x] no
Was the casing pulled? [ ] yes [x] no
Was the casing over drilled? [ ] yes [x] no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used:

From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		

8 WELL PLUGGING MATERIALS

				Material Used		
From 2" 800	feet to	+2	feet	cement	[x] Pumped	[ ] Poured
From 1¼" 380	feet to	+2	feet	cement	[x] Pumped	[ ] Poured
From	feet to		feet		[ ] Pumped	[ ] Poured
From	feet to		feet		[ ] Pumped	[ ] Poured
From	feet to		feet		[ ] Pumped	[ ] Poured
From	feet to		feet		[ ] Pumped	[ ] Poured

Neat Cement Fluid Weight 15.2 lbs/gal
Bentonite Grout % bentonite
Date Started 1/18/2008
Date Completed 1/18/2008

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1942
Signed William Riley by (mH) (By driller performing actual drilling on site or contractor)
Date 1/21/2008

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY