STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 105220
Permit No.
Basin 141

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61281

1. OWNER MGC Resources Inc.
MAILING ADDRESS 2778 Spokane Creek Road
East Helena, MT 57635

ADDRESS AT WELL LOCATION 15 miles north of Tonopah, NV
Hole #MW-WAC
Subdivision Name: County: Nye

2. LOCATION SE ¼ SW ¼ Sec 30 T 05N N/S R 44 E
PERMIT/WAIVER No. M/O-1481 (Issued by Water Resources) Parcel No.

Latitude 38.254131
Longitude 117.084934
UTM E 1616037.456 [x] NAD 27
N 13890449.802 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [x] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [x] RVC
[x] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	30	30
Sil. Ryolite		30	203	173
#8 Sand		203	110	93
32 - 50 lb bags				
3/8" chips		110	40	70
12 bags				
Super Plug		40	0	40
3- 50lb bags				
5 lb bags saccrete				
3' x 3' x 4" surface pad				

Date started: 15-Jan, 20 08
Date completed: 16-Jan, 20 08

9. WELL CONSTRUCTION
Depth Drilled 203 Feet Depth Cased 197 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 3/4	Inches	0	Feet	20	Feet
6	Inches	20	Feet	203	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		1/4" wall	+3	20
2"		Sch 80	+3	197

Perforations:
Type of perforation Horizontal
Size of perforation 0.02

From	Blank +3	feet to	167	feet
From	Screen 167	feet to	187	feet
From	Blank 187	feet to	197 TD	feet
From		feet to		feet
From		feet to		feet

Annular Seal: [x] Yes [ ] No

[ ] Neat Cement	to		[ ] Pumped	[ ] Poured
[ ] Cement Grout	to		[ ] Pumped	[ ] Poured
[ ] Concrete Grout	to		[ ] Pumped	[ ] Poured
[x] ≥30% Bentonite Grout	40	to 0	[x] Pumped	[ ] Poured

Gravel Pack: [x] Yes [ ] No 110 to 203 [x] Pumped [ ] Poured
Type: #8 Sand
Bentonite Chips: [x] Yes [ ] No 110 to 40 [ ] Pumped [x] Poured
Type: 3/8" Bentonite

7. Water Level
Static water level: 110 feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: Cool °F
Quality: Clear

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [x] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
at TD	13.6		

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1698
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 1/25/2008

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY