

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

TT14-MW01

OFFICE USE ONLY  
Log No. 105274  
Permit No. \_\_\_\_\_  
Basin 101

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 54760

1. OWNER DEPT OF NAVY NAS FALLON ADDRESS AT WELL LOCATION 4755 Pastore Rd  
MAILING ADDRESS 4755 Pastore Rd Fallon, NV 89496  
Subdivision Name: NAS FALLON County: Churchill

2. LOCATION SW 1/4 Sec 23 T 18 R 29 E Latitude 39.408269 NAD 27 UTM E 1150353215 NAD 27  
PERMIT/WAIVER No. TRP Longitude 118.703954 N 4363460  NAD 83/WGS 84

Issued by Water Resources Parcel No. DDG-Cell-01

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  Monitor  
 Municipal/Industrial  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
SAND		0'	5'	5'
CLAY		5'	8'	3'
SAND		8'	10'	2'
CLAY		10'	15'	5'
SAND		15'	18'	3'

9. WELL CONSTRUCTION

Depth Drilled 18' Feet Depth Cased 18' Feet

HOLE DIAMETER (BIT SIZE)

From 0 To 18  
Inches Feet Feet Feet  
Inches Feet Feet Feet  
Inches Feet Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>2"</u>		<u>SCH-40</u>	<u>0'</u>	<u>18'</u>

Perforations

Type of perforation Manufactured Slotted  
Size of perforation .010

From 3' feet to 18' feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No

Neat Cement 0' to 1'  Pumped  Poured  
 Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Concrete Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 ≥30% Bentonite Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Gravel Pack:  Yes  No 2 1/2' to 18'  Pumped  Poured  
Type: 2/16 Sand

Bentonite Chips:  Yes  No 1' to 2 1/2'  Pumped  Poured  
Type: 3/8 Bentonite chips

7. Water Level

Static water level: 8' feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: \_\_\_\_\_ °F  
Quality: \_\_\_\_\_

8. WELL TEST DATA

TEST METHOD:  Bailor  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Gregg Drilling Contractor  
Address 950 Howe Rd Contractor  
Maize CA 94553

Nevada contractor's license number issued by the State Contractor's Board C23-0038113  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2328

Signed James Hill  
By driller performing actual drilling on site or contractor  
Date 11.10.07