

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 105326
Permit No. _____
Basin φ51

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59267

1 OWNER Newmont Mining Corp. ADDRESS AT WELL LOCATION Gold Quarry Minesite, about 6 miles north of Carlin, NV
MAILING ADDRESS P.O. Box 669
Carlin, NV 89822 Subdivision Name: _____ County: Eureka

2 LOCATION SW ¼ NE ¼ Sec 2 T 33N N/S R 51 E Latitude 70.779293 UTM E 560929 NAD 27
PERMIT/WAIVER No. 56838 Longitude 116.266853 N 4514348 NAD 83/WGS 84
Issued by Water Resources Parcel No. _____

3 TYPE OF WELL Is this well being plugged because a replacement well was drilled? No Is there an existing well log? Yes
 Domestic Irrigation Test Stock If yes, what is replacement well NOI? _____ If yes, what is NDWR well log #? 70699
 Municipal/Industrial Monitor Stock If yes, what is NDWR well log #? 7450

4 EXISTING WELL CONSTRUCTION

Depth Drilled	320 Feet	Depth Cased	320 Feet
EXISTING CASING SCHEDULE			
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet) To (Feet)
8.625	32	0.3	+2 -320
			400

7 WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: Pumping equipment was pulled, and the well found to be open to original t.d.
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used: No additional perforations were made.

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	To	feet

Type of perforator used:

From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL

Static water level 218 feet below land surface
Artesian flow _____ G.P.M. _____ P.S.I.
Water temperature 60 ° F Quality Good

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
400	feet to	32	Super Plug	<input checked="" type="checkbox"/>	<input type="checkbox"/>
32	feet to	20	Kwik Plug	<input type="checkbox"/>	<input checked="" type="checkbox"/>
20	feet to	0	Neat Cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments

Abandonment procedure was discussed with DWR prior to performing the work. The basic procedure entails circulating the bentonite grout (Super Plug) until it will rise no further, then a bentonite chip (Kwik Plug) bridge. Neat cement is then pumped until it is 20' above the uppermost perforation in the casing. The balance of the casing is filled with clean fill or gravel, as a safety measure.

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 12 % bentonite
Date Started 1/12/2007
Date Completed 1/12/2007

2007 MAY 11 AM 10:48
STATE ENGINEER'S OFFICE

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Eklund Drilling Company, Inc.
Contractor
Address PO Box 2748
Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed Arthur Steelman
By driller performing actual drilling on site or contractor
Date 3/7/2007