

LK-25

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 105328
Permit No.
Basin 651

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59267

1 OWNER Newmont Mining Corp.
MAILING ADDRESS P.O. Box 669
Carlin, NV 89822

ADDRESS AT WELL LOCATION Gold Quarry Minesite, about 6 miles
north of Carlin, NV
Subdivision Name: County: Eureka

2 LOCATION SW 1/4 NE 1/4 Sec 2 T 33N N/S R 51 E
PERMIT/WAIVER No. 56832
Issued by Water Resources Parcel No.

Latitude N 40.777637 UTM E 560794 NAD 27
Longitude W 116.208473 N 4514163 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NO?
Is there an existing well log? Yes
6815
If yes, what is NDWR well log #? 71458

4 EXISTING WELL CONSTRUCTION
Depth Drilled 320 Feet Depth Cased 320 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: Pumping equipment was pulled, and the well found to be open to original t.d.

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8.625	32	0.3	+2	320 100

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used: No additional perforations were made.

Existing Perforations:

Type of perforation	Louver
Size of perforation	0.125"
From 60 60 feet to 400 320 feet	
From	feet to feet

Additional Perforations:

Type of perforator used:	No additional perforations were made.
From	feet to feet Number of perfs per linear foot
From	feet to feet Number of perfs per linear foot
From	feet to feet Number of perfs per linear foot
From	feet to feet Number of perfs per linear foot
From	feet to feet Number of perfs per linear foot
From	feet to feet Number of perfs per linear foot

5 WATER LEVEL
Static water level 185 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 60 °F Quality Good

8 WELL PLUGGING MATERIALS

From	feet to	Material Used	
400	45	Super Plug	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
45	30	Kwik Plug	<input type="checkbox"/> Pumped <input checked="" type="checkbox"/> Poured
30	0	Neat Cement	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments
Abandonment procedure was discussed with DWR prior to performing the work. The basic procedure entails circulating the bentonite grout (Super Plug) until it will rise no further, then a bentonite chip (Kwik Plug) bridge. Neat cement is then pumped until it is 20' above the uppermost perforation in the casing. The balance of the casing is filled with clean fill or gravel, as a safety measure.

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 12 % bentonite
Date Started 1/13/2007
Date Completed 1/13/2007

2007 MAY 11 AM 10:48
STATE ENGINEER SUPERVISOR
21:11:11

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. Contractor
Address PO Box 2748 Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed Arthur Steelman
By driller performing actual drilling on site or contractor
Date 3/7/2007