



STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 105419
Permit No. _____
Basin 131

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 57978

1. OWNER NEWMONT GOLD ADDRESS AT WELL LOCATION PHOENIX MINE
MAILING ADDRESS P.O BOX 669
Carlin, NV 89822

2. LOCATION NW 1/4 SW 1/4 Sec 9 T 30N N/S R 43 E Latitude 40°46'33.2 UTM E NAD 27
PERMIT/WAIVER No. 54214 Longitude 117°15'43.9 N NAD 83/WGS 84
Issued by Water Resources Parcel No. _____ Subdivision Name: _____ County: Lander

3. TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
Is this well being plugged because a replacement well was drilled? YES
If yes, what is replacement well NOI? _____
Is there an existing well log? YES
If yes, what is NDWR well log #? 23267

4. EXISTING WELL CONSTRUCTION
Depth Drilled 408 Feet Depth Cased 408 Feet
EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		1/4	0	168

7. WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:

Existing Perforations:
Type of perforation ROSCOE MOSS SHUTTER SCREEN
Size of perforation 1/8

From	feet to	feet	feet
From <u>168</u>	feet to	<u>288</u>	feet
From <u>288</u>	feet to	<u>408</u>	feet
From _____	feet to	_____	feet
From _____	feet to	_____	feet

Type of perforator used: Holte Air Perforator

From	feet to	feet	Number of perfs per linear foot
From <u>50</u>	feet to	<u>168</u>	<u>4</u>
From _____	feet to	_____	_____
From _____	feet to	_____	_____
From _____	feet to	_____	_____
From _____	feet to	_____	_____

5. WATER LEVEL
Static water level 87 feet below land surface
Artesian flow no G.P.M. _____ P.S.I. _____
Water temperature _____ °F Quality _____

8. WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From <u>20</u>	feet to	<u>408</u>	<u>abandonite</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From <u>0</u>	feet to	<u>20</u>	<u>NEAT CEMENT</u>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
From _____	feet to	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
From _____	feet to	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
From _____	feet to	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
From _____	feet to	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>

6. Additional Notes or Comments
Used 4,000 Gallons Water & 150 50# Sacks Bentonite Super Plug to Mix Grout
N 40.463421
W 117.153445 NAD27
Rev

Neat Cement Fluid Weight 16 lbs/gal
Bentonite Grout 19 % bentonite
Date Started 9/26/2006
Date Completed 9/27/2006

9. DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources Nevada, Inc. dba Humboldt Drilling & Pump Contractor
Address 4975 W. Winnemucca Blvd. Winnemucca, NV 89445 Contractor
Nevada contractor's license number issued by the State Contractor's Board 56797
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2099
Signed Judi Leach, Office
By driller performing actual drilling of site or contractor
Date 11/7/06