


LK-32

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT



OFFICE USE ONLY

Log No. 105609
Permit No.
Basin (DS)

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59268

1 OWNER Newmont Mining Corp.
MAILING ADDRESS P.O. Box 669
Carlin, NV 89822

ADDRESS AT WELL LOCATION Gold Quarry Minesite, about 6 miles
north of Carlin, NV
Subdivision Name:
County: Eureka

2 LOCATION NW 1/4 NE 1/4 Sec 2 T 33N N/S R 51 E
PERMIT/WAIVER No. 56838
Issued by Water Resources Parcel No.

Latitude UTM E 567170 NAD 27
Longitude N 4514670 NAD 83/WGS 84

3 TYPE OF WELL
[ ] Domestic [ ] Irrigation [ ] Test
[X] Municipal/Industrial [ ] Monitor [ ] Stock

Is this well being plugged because a
replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
7/2/8
71438
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION
Depth Drilled 320 Feet Depth Cased 320 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [ ] yes [X] no
If well was not cleaned out to total depth, please explain why: Pumping equipment
was pulled, and the well found to be open to original t.d.

Table with 5 columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet). Row 1: 8.625, 32, 0.3, +2, 320.

Was the well contaminated? [ ] yes [X] no
Was the casing pulled? [ ] yes [X] no
Was the casing over drilled? [ ] yes [X] no
If casing was left in place, please show where additional perforations were made:

Existing Perforations:
Table with 4 columns: From, Type of perforation, Louver, To. Row 1: 60, Size of perforation, 0.125", 320.

Additional Perforations:
Type of perforator used: No additional perforations were made.
Table with 4 columns: From, feet to, feet, Number of perfs per linear foot.

5 WATER LEVEL
Static water level 280 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 60 °F Quality Good

8 WELL PLUGGING MATERIALS
Material Used
Table with 4 columns: From, feet to, feet, Material Used. Rows include Super Plug, Kwik Plug, Neat Cement, Clean Fill/Gravel.

6 Additional Notes or Comments
Abandonment procedure was discussed with DWR prior to
performing the work. The basic procedure entails circulating
the bentonite grout (Super Plug) until it will rise no further, then
a bentonite chip
(Kwik Plug) bridge. Neat cement is then pumped until it is 20'
above the uppermost perforation in the casing. The balance of
the casing is filled with clean fill or gravel, as a safety measure.

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 12 % bentonite
Date Started 1/10/2007
Date Completed 1/10/2007

71-1111 6-01111002

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true
to the best of my knowledge.
Name Eklund Drilling Company, Inc. Contractor
Address PO Box 2748 Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed Arthur Steelman
By driller performing actual drilling on site or contractor
Date 3/7/2007