

LK-17

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY

Log No. 105611
Permit No.
Basin (05)

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59268

1 OWNER Newmont Mining Corp.
MAILING ADDRESS P.O. Box 669
Carlin, NV 89822

ADDRESS AT WELL LOCATION Gold Quarry Minesite, about 6 miles
north of Carlin, NV
Subdivision Name:
County: Eureka

2 LOCATION SW 1/4 NE 1/4 Sec 2 T 33N N/S R 51 E
PERMIT/WAIVER No. 56838
Issued by Water Resources Parcel No.

Latitude UTM E 567170
Longitude N 4514870
NAD 27
NAD 83/WGS 84

3 TYPE OF WELL
Domestic
Municipal/Industrial
Irrigation
Monitor
Test
Stock

Is this well being plugged because a
replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #? 74460

4 EXISTING WELL CONSTRUCTION
Depth Drilled 320 Feet
Depth Cased 320 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes [X] no

Table with columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet). Row 1: 8.625, 32, 0.3, +2, 320.

If well was not cleaned out to total depth, please explain why: Pumping equipment
was pulled, and the well found to be open to original t.d.

Existing Perforations table with columns: Type of perforation, Size of perforation, From, To.

Was the well contaminated? yes [] no [X]
Was the casing pulled? yes [] no [X]
Was the casing over drilled? yes [] no [X]

If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used: No additional perforations were made.

5 WATER LEVEL
Static water level 180 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 60 ° F Quality Good

8 WELL PLUGGING MATERIALS
Material Used

6 Additional Notes or Comments
Abandonment procedure was discussed with DWR prior to
performing the work. The basic procedure entails circulating
the bentonite grout (Super Plug) until it will rise no further, then
a bentonite chip (Kwik Plug) bridge. Neat cement is then pumped until it is 20'
above the uppermost perforation in the casing. The balance of
the casing is filled with clean fill or gravel, as a safety measure.

Table with columns: From, To, Material Used, Pumped/Poured. Rows include Super Plug, Kwik Plug, Neat Cement, Clean Fill/Gravel.

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 12 % bentonite
Date Started 1/11/2007
Date Completed 1/11/2007

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true
to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Address PO Box 2748
Elko, NV 89803
Nevada contractor's license number 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1776
Signed Arthur Steelman
Date 3/7/2007