STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 105740
Permit No.
Basin 066

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 58647

1 OWNER Newmont Mining Corporation
MAILING ADDRESS PO Box 388
SW Valmy, NV 89438

ADDRESS AT WELL LOCATION Twin Creeks Mine
Subdivision Name: *County:* Humboldt

2 LOCATION ~~SE~~ ¼ NE~~SE~~ ¼ Sec 18 T 39N *N/S* R 43 *E*
PERMIT/WAIVER No. M/O-1130B *Issued by Water Resources* 7-091-04 *Parcel No.*

Latitude 41.263461
Longitude 117.170165
UTM E 485745.6170
N 4567806.04422
☒ NAD 27 ☐ NAD 83/WGS 84

3 TYPE OF WELL
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI?

Is there an existing well log? YES
If yes, what is NDWR well log #? 74183

4 *EXISTING WELL CONSTRUCTION*
Depth Drilled 1000 Feet Depth Cased 1000 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.5	PVC	.250	0	1000

Existing Perforations:
Type of perforation SLOT
Size of perforation 0.02

From	300	feet to	1000	feet
From		feet to		feet
From		feet to		feet
From		feet to		feet
From		feet to		feet

5 *WATER LEVEL*
Static water level DRY feet below land surface
Artesian flow G.P.M. P.S.I
Water temperature °F Quality

6 Additional Notes or Comments
Pumped neat cement down trimmy from bottom to surface.
Neat cement weighted 155. Total volume pumped was 375 gal
using 40 each 94 lb. bags of cement.

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☒ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☐ yes ☒ no
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used:

From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		
From	feet to	feet	Number of perfs per linear foot		

8 WELL PLUGGING MATERIALS

				Material Used		
From	0	feet to	1000 feet	CEMENT	☒ Pumped	☐ Poured
From		feet to	feet		☐ Pumped	☐ Poured
From		feet to	feet		☐ Pumped	☐ Poured
From		feet to	feet		☐ Pumped	☐ Poured
From		feet to	feet		☐ Pumped	☐ Poured
From		feet to	feet		☐ Pumped	☐ Poured

Neat Cement Fluid Weight 15.5 lbs/gal
Bentonite Grout % bentonite
Date Started 21-Jun-07
Date Completed 21-Jun-07

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1777
Signed Dennis L. White by [illegible] (By driller performing actual drilling on site or contractor)
Date 21-Jun-07

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY