

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT



OFFICE USE ONLY
Log No. 105918
Permit No. _____
Basin 766

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61312

1 OWNER Newmont Mining Corp. ADDRESS AT WELL LOCATION Twin Creeks Mine
MAILING ADDRESS PO Box 669 Hole #DW37
Carlin, NV 89822 Subdivision Name: _____ County: Humboldt

2 LOCATION NW 1/4 NE 1/4 Sec 30 T 39N N/S R 43 E Latitude 41.236745 UTM E 485813.9857 NAD 27
PERMIT/WAIVER No. 70662T Longitude 117.169280 N 4564840.0193 NAD 83/WGS 84
Issued by Water Resources Parcel No. _____

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI? _____
Is there an existing well log? Yes
If yes, what is NDWR well log #? 88422

4 EXISTING WELL CONSTRUCTION
Depth Drilled 600 Feet Depth Cased 600 Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16			0	600

Existing Perforations:

Type of perforation	From	To
Louvered	0	600
Size of perforation	0.125	

5 WATER LEVEL
Static water level 129 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature warm °F Quality Clear

6 Additional Notes or Comments
Attn: Coordinates on original well log are wrong.
Check static on water level - move rig over hole and put pipe into bottom and tag bottom. Hole is clean, pump bentonite slurry from bottom to top - a total of 13,200 gal (287 sacks super plus). Fluid level above static 57'. Pour in 2 super sack 3/8" hole plug up to 20' below surface then pour in 400 gallons cement slurry (43 sacks cement)

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used:
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____
From _____ feet to _____ feet Number of perfs per linear foot _____

8 WELL PLUGGING MATERIALS
Material Used
From 600 feet to 72 feet Bentonite Grout Pumped Poured
From 72 feet to 20 feet 3/8" Hole Plug Pumped Poured
From 20 feet to 0 feet Neat Cement Pumped Poured
From _____ feet to _____ feet _____ Pumped Poured
From _____ feet to _____ feet _____ Pumped Poured
From _____ feet to _____ feet _____ Pumped Poured

Neat Cement Fluid Weight 15.2 lbs/gal
Bentonite Grout 30 % bentonite
Date Started 3/22/2008
Date Completed 3/23/2008

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Contractor
Address PO Box 2748
Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
Signed Donald School By driller performing actual drilling on site or contractor
Date 4/9/2008