STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 106027
Permit No.
Basin 066

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61287

1. OWNER Barrick Gold Exploration
MAILING ADDRESS 293 Spruce Road
Elko, NV 89801

ADDRESS AT WELL LOCATION 19 milese NE of Golconda, NV
Hole #RPZ3N
Subdivision Name: County: Humboldt

2. LOCATION NE ¼ SE ¼ Sec 33 T 38N N/S R 42 E
PERMIT/WAIVER No. NEV2005102
Issued by Water Resources Parcel No.

Latitude 41.126355
Longitude 117.24265
UTM E 479631.11 [x] NAD 27
N 4552600.05 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [x] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [x] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium		0	140	140
32 Bags of #8 Sand 50 lb. each				
2 Bags of 3/8" chips 50 lb. each				
16 Bags of cement 94 lb. each				

Date started: 27-Jan , 20 08
Date completed: 27-Jan , 20 08

7. *Water Level*
Static water level: Dry feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
N/A		

9. *WELL CONSTRUCTION*
Depth Drilled 140 Feet Depth Cased 138 ~~140~~ Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8 3/4	Inches	0	Feet	20	Feet
5 7/8	Inches	20	Feet	140	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
1	Nominal	Sch. 80	+2	138

Perforations:
Type of perforation Slotted
Size of perforation 0.02
From 58 feet to 138 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [x] Yes [ ] No
[x] Neat Cement 0 to 50 [ ] Pumped [x] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [x] Yes [ ] No 55 to 140 [ ] Pumped [x] Poured
Type: #8 Sand
Bentonite Chips: [x] Yes [ ] No 50 to 55 [ ] Pumped [x] Poured
Type: 3/8" Hole Plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Contractor
Address PO Box 2748
Contractor
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2260
Signed Reese Schoerl
By driller performing actual drilling on site or contractor
Date 2/22/2008

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY