

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
 WELL DRILLER'S REPORT

OFFICE USE ONLY

Log No. 106199
 Permit No. _____
 Basin 071

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62653

1. OWNER Don & Michelle Spence ADDRESS AT WELL LOCATION 9445 Sabin
 MAILING ADDRESS 6400 Nugget Drive - Winnemucca NV Winnemucca, NV 89445
 SE
 2. LOCATION SW 1/4 NE 1/4 Sec 30 T35N/S R38E Latitude N40°88'106 UTM E NAD 27
 PERMIT/WAIVER NO. 010-645-14 Longitude W117°73'733 N NAD 83/WGS 84
 Issued by Water Resources Parcel No. _____
 Subdivision Name: Tycanna County: Humboldt

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sand/course gravel		0	50	50
Clay - cobbles		50	60	10
Boulders		60	90	30
Clay/Sand		90	135	45
Course gravel/ cobbles		135	150	15
Clay/cobbles		150	200	50
Course sand/gravel		200	235	35
Clay/cobbles		235	300	65
Boulders	X	300	320	20
Clay		320	350	30
Gravel/sand	X	350	395	45

N 40.681171
 W 117.736362 NAD27

9. WELL CONSTRUCTION
 Depth Drilled 395 Feet Depth Cased 395 Feet
 HOLE DIAMETER (BIT SIZE)
 From _____ To _____
12 Inches 0 Feet 200 Feet
11 Inches 200 Feet 395 Feet
 _____ Inches _____ Feet _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	10	1.88	+1	20
6.625	4.06	.516	20	395

Perforations:
 Type of perforation Factory Cut
 Size of perforation 050
 From 355 feet to 395 feet
 From _____ feet to _____ feet

Annular Seal: Yes No
 Neat Cement 0 to 50 Pumped Poured
 Cement Grout _____ to _____ Pumped Poured
 Concrete Grout _____ to _____ Pumped Poured
 ≥30% Bentonite Grout _____ to _____ Pumped Poured
 Gravel Pack: Yes No 50 to 395 Pumped Poured
 Type: _____
 Bentonite Chips: Yes No _____ to _____ Pumped Poured
 Type: _____

Date started: June 5, 20 08
 Date completed: June 9, 20 08

7. Water Level
 Static water level: 300 feet below land surface
 Artesian Flow: N/A G.P.M. N/A P.S.I.
 Water Temperature: Cool °F
 Quality: Good

8. WELL TEST DATA

TEST METHOD:	<input type="checkbox"/> Bailer	<input checked="" type="checkbox"/> Pump	<input type="checkbox"/> Air Lift
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	
<u>11</u>		<u>12</u>	

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Fred Anderson Drilling, Inc.
 (CONTRACTOR)
 Address 10760 S. Grass Valley Road
 (CONTRACTOR)
Winnemucca, NV 89445
 Nevada contractor's license number issued by the State Contractor's Board 021467
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2083
 Signed Fred Anderson Drilling, Inc.
 By driller performing actual drilling on site or contractor
 Date June 16, 2008