

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
 Log No. 106548
 Permit No. _____
 Basin 069
 NOTICE OF INTENT NO. 61572

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

1 OWNER WINNEMUCCA FARMS, INC. ADDRESS AT WELL LOCATION _____
 MAILING ADDRESS One Potato Road Well # 8A
Winnemucca, NV 89445 Subdivision Name: _____ County: Humboldt

2 LOCATION SW ¼ SW ¼ Sec 29 T 39N N/S R 39 E Latitude 41°13.370 UTM E _____ NAD 27
 PERMIT/WAIVER No. 34080-2 67467T Longitude 117°37.188 N _____ NAD 83/WGS 84
Issued by Water Resources Parcel No.

3 TYPE OF WELL Domestic Irrigation Test Municipal/Industrial Monitor Stock
 Is this well being plugged because a replacement well was drilled? Yes
 If yes, what is replacement well NOI? 61571
 Is there an existing well log? Yes
 If yes, what is NDWR well log #? 84536

4 EXISTING WELL CONSTRUCTION

Depth Drilled	<u>615</u> Feet	Depth Cased	<u>615</u> Feet
---------------	-----------------	-------------	-----------------

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>18</u>	<u>70#</u>	<u>.375</u>	<u>+1</u>	<u>615</u>

7 WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? yes no
 If well was not cleaned out to total depth, please explain why:
Pump was stuck securely in the well. Well caved in above pump bowls.

Was the well contaminated? yes no
 Was the casing pulled? yes no
 Was the casing over drilled? yes no
 If casing was left in place, please show where additional perforations were made:
 Additional Perforations: NA

Type of perforator used:	From	feet to	feet	Number of perfs per linear foot

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet
<u>Wire Wrap Screen</u>	<u>0.035</u>			

5 WATER LEVEL

Static water level 56 feet below land surface
 Artesian flow NA G.P.M. _____ P.S.I. _____
 Water temperature _____ ° F Quality _____

8 WELL PLUGGING MATERIALS

Material Used	From	feet to	feet	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured

6 Additional Notes or Comments

Pump stuck in well. It would not move. We cut pump column off below discharge head. Pump column was full of water. Water in casing was at 50 feet. Ran tremie as far as possible between casing and pump column. Pumped 1350 gallons 20% bentonite slurry. Ran tremie into pump column and pumped 4 cu. yards cement grout into pump column and upper 10 feet of annulus. Well was caved in at about 210 feet.

N41.722947
W 117.618831 NAD27

Neat Cement Fluid Weight _____ lbs/gal
 Bentonite Grout 20 % bentonite
 Date Started 5/13/2008
 Date Completed 5/14/2008

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling and Pump Co.
Contractor

Address 4975 W. Winnemucca Blvd.
Contractor
Winnemucca, Nevada 89445

Nevada contractor's license number 56797
 issued by the State Contractor's Board

Nevada driller's license number issued by the 2158
 Division of Water Resources, the on-site driller

Signed Jodi Leach, Office
By driller performing actual drilling on site or contractor

Date 5/23/2008