

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY 106557
Log No.
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61354

1 OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 388
Valmy, NV 89435

ADDRESS AT WELL LOCATION Twin Creeks Mine
Hole #TMO-10001
Subdivision Name: _____ County: Humboldt

2 LOCATION NW ¼ SW ¼ Sec 10 T 39N N/S R 43 E
PERMIT/WAIVER No. M/O-1497
Issued by Water Resources Parcel No. _____

Latitude 41.972938 UTM E 489743.351 NAD 27
Longitude 117.122459 N 4568851.3843 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI? _____

Is there an existing well log? yes
If yes, what is NDWR well log #? _____

4 EXISTING WELL CONSTRUCTION
Depth Drilled 800 Feet Depth Cased _____ Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: well was never completed. There was no casing in it.

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
None				

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used: _____ no well casing in hole

Existing Perforations:

Type of perforation	No well casing in hole			
Size of perforation	From	feet to	feet	feet
	From	feet to	feet	feet
	From	feet to	feet	feet
	From	feet to	feet	feet
	From	feet to	feet	feet

Type of perforator used:	From	feet to	feet	Number of perfs per linear foot
	From	feet to	feet	Number of perfs per linear foot
	From	feet to	feet	Number of perfs per linear foot
	From	feet to	feet	Number of perfs per linear foot
	From	feet to	feet	Number of perfs per linear foot
	From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
Static water level 180 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature _____ °F Quality Poor

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From	24	feet to 800	feet bentonite grout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From	0	feet to 24	feet cement	<input type="checkbox"/>	<input checked="" type="checkbox"/>
From		feet to	feet	<input type="checkbox"/>	<input type="checkbox"/>
From		feet to	feet	<input type="checkbox"/>	<input type="checkbox"/>
From		feet to	feet	<input type="checkbox"/>	<input type="checkbox"/>
From		feet to	feet	<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments
Client opted to abandon hole and not make a well because of bad ground conditions and the chance of a poor well and casing won't go to Bottom. So we abandoned hole as per NDWR regulations for abandonment of an existing monitor well. Pumped 1790 gal bentonite grout slurry - (39 sks super plug) in hole and poured in 12 sks 3/8" hole plug (50# sks and tagged plug @ 24". Then poured in 60 gal of neat cement (6 1/2 sks cement) to make a cement surface seal.

Neat Cement Fluid Weight 16 lbs/gal
Bentonite Grout 12.5 % bentonite
Date Started 6/2/2008
Date Completed 6/2/2008

STATE ENGINEERS OFFICE
2008 JUN 25 AM 11:49

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. Contractor
Address PO Box 2748 Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
Signed Donald Schoorel by (ma)
By driller performing actual drilling on site or contractor
Date 6/2/2008