

**STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY 106641  
Log No. \_\_\_\_\_  
Permit No. \_\_\_\_\_  
Basin 287

**PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK**

*Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 63135

1 OWNER Horseshoe Bend LLC  
MAILING ADDRESS PO Box 1209  
Reno, NV 89504

ADDRESS AT WELL LOCATION Corner of Foothill and Vera  
Reno, NV 89511  
Subdivision Name \_\_\_\_\_ County Washoe

2 LOCATION NE 1/4 SE 1/4 Sec 7 T 18N N/S R 20 E  
PERMIT/WAIVER No. 044-371-11  
Issued by Water Resources Parcel No.

Latitude 39.43898 UTM E \_\_\_\_\_  NAD 27  
Longitude 119.77196 N \_\_\_\_\_  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? no  
If yes, what is replacement well NOI? \_\_\_\_\_

Is there an existing well log? yes  
If yes, what is NDWR well log #? 22385

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 150 Feet Depth Cased 150 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	16.9	188	0	50

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations: \_\_\_\_\_

Existing Perforations:

Type of perforation	Size of perforation	From	To
<u>factory</u>	<u>1/8</u>	<u>130</u> feet to	<u>150</u> feet

Type of perforator used: Mills Knife

From	To	Number of perfs per linear foot
<u>30</u> feet to	<u>130</u> feet	<u>5</u>

5 WATER LEVEL  
Static water level 14' feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature cold °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

From	To	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<u>0</u> feet to	<u>20</u> feet	<u>neat cement</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<u>20</u> feet to	<u>150</u> feet	<u>bentonite grout</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments

N 39.439069  
W 119.770939 NAD83

RECEIVED  
 2008 AUG 25 PM 1:57  
 STATE ENGINEERING CENTER

Neat Cement Fluid Weight 15.5 lbs/gal  
Bentonite Grout 20% % bentonite  
Date Started 8/15/2008  
Date Completed 8/16/2008

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name McKay Drilling Inc. Contractor  
Address 4850 Joule St #A5 Contractor  
Reno, NV 89502

Nevada contractor's license number issued by the State Contractor's Board 14170  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2121

Signed [Signature] By driller performing actual drilling on site or contractor  
Date 8/21/2008