STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 107208
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Clark Co.

NOTICE OF INTENT NO. 34922

1. OWNER Public Right of Way
MAILING ADDRESS

ADDRESS AT WELL LOCATION Public Right of Way
APN 162-10-399-003
Subdivision Name: County: Clark

2. LOCATION NW¼ SW¼ Sec 10 T 21 S R 61 E
PERMIT/WAIVER No. 8-000841-6 162-10-399-003
Issued by Water Resources Parcel No.

Latitude N 36° 8.067
Longitude W 115° 9.282
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
asphalt		0	.5	.5
aggregate base		.5	1.5	1.0
silty sand		1.5	3.5	2.0
clayey sand		3.5	4.5	1.0
cemented sand+gravel		4.5	6.5	2.0
sandy clay		6.5	12	5.5
silty gravel		12	15	3
clayey sand		15	16.5	1.5
silty gravel		16.5	21	4.5
sandy clay		21	24.5	3.5
clayey gravel		24.5	31	6.5
cemented sand+gravel		31	34	3
MW-17				

Date started: Sept 15, 20 08
Date completed: Sept. 15, 20 08

9. WELL CONSTRUCTION
Depth Drilled 34 Feet Depth Cased 34 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	34	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Sch 40 PVC	0	34

Perforations:
Type of perforation Machine slotted
Size of perforation .020"
From 19 feet to 34 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☐ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 3 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 12' to 34' ☐ Pumped ☐ Poured
Type: silica sand #12
Bentonite Chips: ☒ Yes ☐ No 3.0' to 12.0' ☐ Pumped ☒ Poured
Type: 3/8" chips

7. Water Level
Static water level: 21.4 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

DCNR/DWR RECEIVED
OCT 14 2008
LAS VEGAS OFFICE

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name TERRACON
Contractor
Address 750 PILOT ROAD
Contractor
LAS VEGAS, NV 89119
Nevada contractor's license number issued by the *State Contractor's Board*
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 12097
Signed
By driller performing actual drilling on site or contractor
Date

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY