STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 107228
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 34952

1. OWNER Somerset Shopping Center, LP
MAILING ADDRESS 294 Convention Ctr. Dr. LV, NV
ADDRESS AT WELL LOCATION 252 Convention Center LV, NV
Subdivision Name: County: Clark

2. LOCATION SW ¼ SE ¼ Sec 09 T 21 N/S R 61 E
PERMIT/WAIVER No. MDEP 070621-02 (Issued by Water Resources) APN 162-09-802-001 Parcel No.
Latitude 36.13279 °N
Longitude -115.16047 °W
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
asphalt		0	0.25	.25
gravelly sand		0.25	2	1.75
silty sand		2	3	1
clayey sand		3	4.5	1.5
sandy clay		4.5	7.5	3
clayey sand		7.5	9.5	2
silty gravel		9.5	12	2.5
cemented sand + gravel		12	15	3
silty gravel		15	18	3
cemented sand + gravel		18	21	3
sandy clay		21	23.5	2.5
clayey sand		23.5	27	3.5
cemented sand + gravel		27	28.5	1.5
silty sand		28.5	30	1.5
cemented sand + gravel		30	34	4
MW-8				

Date started: 9-9, 20 08
Date completed: 9-9, 20 08

7. Water Level
Static water level: 29.19 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled 34 Feet Depth Cased 34 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 Inches	0 Feet	34 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		sch 40 PVC	0	34

Perforations:
Type of perforation machine slotted
Size of perforation .020
From 19 feet to 34 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☐ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 4 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 17 to 34 ☐ Pumped ☒ Poured
Type: Silica sand #12
Bentonite Chips: ☒ Yes ☐ No 4 to 17 ☐ Pumped ☒ Poured
Type: 3/8" chips

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name TERRACON (Contractor)
Address 750 PILOT ROAD (Contractor)
LAS VEGAS, NV 89119
Nevada contractor's license number issued by the *State Contractor's Board*
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2097
Signed (By driller performing actual drilling on site or contractor)
Date

DCNR/DWR RECEIVED OCT 14 2008 LAS VEGAS OFFICE

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY