STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 107470
Permit No.
Basin Ø66

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61063

1. OWNER Barrick/Pinson Mining Co.
MAILING ADDRESS HC66 Box 2
Golconda, NV 89414-9602

ADDRESS AT WELL LOCATION Pinson Mine
Subdivision Name: County: Humboldt

2. LOCATION SE ¼ SE ¼ Sec 29 T 38N N/S R 42 E
PERMIT/WAIVER No. NEV89002
Issued by Water Resources Parcel No.

Latitude N 41.137340
Longitude W 117.261185
UTM E 478079
N 4553824
[X] NAD 27
[ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
San		0	40	40
Limestone		40	460	420
Shale		460	940	480
Limestone		940	1120	180
Green Clay		1120	1160	40
Limestone		1160	1300	140

Date started: 19-Nov , 20 08
Date completed: 2-Dec , 20 08

9. WELL CONSTRUCTION
Depth Drilled 1300 Feet Depth Cased 1300 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12	Inches	0	Feet	40	Feet
7	Inches	40	Feet	1120	Feet
6 3/4	Inches	1120	Feet	1300	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375		Sch. 40	+1.5	1298.5

Perforations:
Type of perforation Slot
Size of perforation 0.04
From 1198.5 feet to 1278.5 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 0 to 50 [ ] Pumped [X] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured
Gravel Pack: [X] Yes [ ] No 1195 to 1300 [ ] Pumped [X] Poured
Type: #8 Sand
Bentonite Chips: [X] Yes [ ] No 50 to 1195 [ ] Pumped [X] Poured
Type: 3/8" Chips

7. Water Level
Static water level: 531 feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: Cool °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1220 Ft.	60		20 min.

STATE ENGINEERS OFFICE
2008 DEC 10 AM 11:08

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Contractor
Address PO Box 2748
Contractor
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2260
Signed Reese Schorzl by (MH)
By driller performing actual drilling on site or contractor
Date 12/2/2008

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY