STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 107799
Permit No.
Basin Ø44

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62846

1. OWNER JOHN W. STENOVICH
MAILING ADDRESS 186 RYNDON, UNIT 11
ELKO, NV 89801-9407

ADDRESS AT WELL LOCATION 5613 VAN BUREN AVE
RYNDON AREA
Subdivision Name: Twin River Rancho #4 County: ELKO

2. LOCATION NW ¼ SW ¼ Sec 5 T 35N N/S R 57 E
PERMIT/WAIVER No. 026-013-008
Issued by Water Resources Parcel No.

Latitude 40.947170
Longitude 115.578841
UTM E 11T 0619622 [X] NAD 27
N 4533653 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOPSOIL		0	5	5
GRAVEL W/CLAY		5	40	35
MED/SOFT SANDSTONE		40	90	50
GRAVEL	XX	90	160	70

Date started: 15-Oct, 20 08
Date completed: 15-Oct, 20 08

9. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased 160 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	160	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	13	.188 STEEL	+2	20
6.625		SDR-21 PLASTIC	20	160

Perforations:
Type of perforation FACTORY SDR-21 PLASTIC SCREEN
Size of perforation 1/0/1900
From 120 feet to 160 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 0 to 15 [ ] Pumped [X] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 55 to 160 [ ] Pumped [X] Poured
Type: 3/8" PEA GRAVEL
Bentonite Chips: [X] Yes [ ] No 15 to 55 [ ] Pumped [X] Poured
Type: 3/8" BENTONITE CHIPS

7. Water Level
Static water level: 76 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: COLD °F
Quality: GOOD

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
50		1

STATE ENGINEERS OFFICE
2008 OCT 30 AM 11:41
RECEIVED

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC. (Contractor)
Address P. O. BOX 850 (Contractor)
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1166
Signed (By driller performing actual drilling on site or contractor)
Date 10/28/2008

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY