


STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY 108352



Log No. \_\_\_\_\_  
Permit No. \_\_\_\_\_  
Basin 11QB

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. \_\_\_\_\_ 61623

OK  
OK  
OK

1. OWNER Hawthorne Army Depot  
MAILING ADDRESS 15 Maine St  
Hawthorne, NV 89415

ADDRESS AT WELL LOCATION \_\_\_\_\_  
Subdivision Name: \_\_\_\_\_ County: Mineral

2. LOCATION NE 1/4 SE 1/4 Sec 32 T 08N N/S R 30 E  
PERMIT/WAIVER No. OK OK OK #8

Latitude \_\_\_\_\_ UTM E 38,59 672  NAD 27  NAD 83/WGS 84  
Longitude \_\_\_\_\_ N 118,65 421

Issued by Water Resources Parcel No. \_\_\_\_\_

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other Abandon

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
30% Solids Grout		0	26.50	27
14.2 Gallons per bag				
2.2 CF yield				
Dug out 5' capped with concrete				
<u>DO NAD 27</u> <u>38,596,799 NW</u> <u>118,653,241 SW</u>				

9. WELL CONSTRUCTION

Depth Drilled	Feet	Depth Cased	Feet
HOLE DIAMETER (BIT SIZE)			
	From	To	
	Inches	Feet	Feet
	Inches	Feet	Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		Sch 40 PVC	0	26.5

Perforations:

Type of perforation	Size of perforation	From	feet to	feet
		From	feet to	feet
		From	feet to	feet
		From	feet to	feet
		From	feet to	feet
		From	feet to	feet

Annular Seal:  Yes  No

<input type="checkbox"/> Neat Cement	0 to 10	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Cement Grout	to	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input type="checkbox"/> Concrete Grout	to	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<input checked="" type="checkbox"/> 30% Bentonite Grout	10 to 26.5	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
Gravel Pack:	<input type="checkbox"/> Yes <input type="checkbox"/> No	to	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
Type:			
Bentonite Chips:	<input type="checkbox"/> Yes <input type="checkbox"/> No	to	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
Type:			

Date started: 16-Mar 20 09  
Date completed: 16-Mar 20 09

7. Water Level  
Static water level: 18.83 feet below land surface  
Artesian Flow: NA G.P.M. P.S.I.  
Water Temperature: NA °F  
Quality: \_\_\_\_\_

8. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name WDC Exploration & Wells Contractor  
Address PO Box 141 Contractor  
Zamora, CA 95698  
Nevada contractor's license number issued by the State Contractor's Board 12852  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2111  
Signed [Signature] By driller performing actual drilling on site or contractor  
Date 3/17/2009

RECEIVED  
JUL 09 2009  
STATE ENGINEER'S OFFICE

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY