WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 108806
Permit No.
Basin 044

NOTICE OF INTENT NO. 64020

1. OWNER Queenstake Resources
MAILING ADDRESS HC-31 Box 78 ELKO NV. 89801 SW
ADDRESS AT WELL LOCATION Queenstake Resources Jerritt Canyon

2. LOCATION NW ¼ SW ¼ Sec. 34 T. 41 N/S R. 54 E/W ELKO County
PERMIT NO. (Issued by Water Resources) | Parcel No. water Pollution Control # NEV0000020 | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. ~~PROPOSED USE~~ RECHARGE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill		0'	20'	20'
Sand		20'	35'	15'
Sand & CLAY		35'	45'	10'
Sand with Gravel		45'	120	75'

41.402420°N
115.885544°W
NAD 27 (12)

Clean Well for 5½ Hrs.

UTME 1945799
UTMN 15039433
NAD-83 US FEET

Date started 7-12, 2009
Date completed 7-16, 2009

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
98'	6.8	[illegible]	5½ Hrs.

8. WELL CONSTRUCTION
Depth Drilled ____ Feet Depth Cased ____ Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12"	Inches	0'	Feet	20'	Feet
10"	Inches	20'	Feet	120'	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5½"	3.5	3/8"		
		Sched. 80		
		PVC		

Perforations:
Type perforation Horz. slot Sched. 80
Size perforation 0.040 PVC
From 110' feet to 30' feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet
From ____ feet to ____ feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 19'
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 110' feet to 25' feet

9. WATER LEVEL
Static water level 9' feet below land surface
Artesian flow ND 6.8 G.P.M. 6.8-100 S.I.
Water temperature 54° °F Quality Clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Ward Weaver
Address 1074 Barrington AVE. ELKO, NV. (Contractor)
Rimrock Drilling (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 0030630
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676
Signed Ward Weaver (By driller performing actual drilling on site or contractor)
Date 7-16-09

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627