


STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY 118818

Log No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Basin 83



PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in  
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64122

1 OWNER Waste Management ADDRESS AT WELL LOCATION Lockwood Landfill  
 MAILING ADDRESS 2401 Canyon Way Sparks, NV 89431 21 Sparks, Nevada  
 Subdivision Name: \_\_\_\_\_ County: Washoe

2 LOCATION NW ¼ SE ¼ Sec 22 T 19N N/S R 20 E Latitude 39.497661 UTM E  NAD 27  
 PERMIT/WAIVER No. M/O 1527 04-111-20 Longitude 119.61477 N  NAD 83/WGS 84  
Issued by Water Resources Parcel No.

3 TYPE OF WELL Is this well being plugged because a replacement well was drilled? no Is there an existing well log? yes  
 Domestic  Irrigation  Test  Stock If yes, what is replacement well NDI? \_\_\_\_\_ If yes, what is NDWR well log #? 107939  
 Municipal/Industrial  Monitor

4 EXISTING WELL CONSTRUCTION  
 Depth Drilled 545 Feet Depth Cased 0 Feet

7 WELL PLUGGING PROCEDURE  
 Was well cleaned out to total depth?  yes  no  
 If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Was the well contaminated?  yes  no  
 Was the casing pulled?  yes  no  
 Was the casing over drilled?  yes  no  
 If casing was left in place, please show where additional perforations were made:  
 Additional Perforations:  
 Type of perforator used: \_\_\_\_\_

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet

Additional Perforations:

Type of perforator used:	From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL  
 Static water level dry feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	Pumped	Poured
0	feet to	530	cement grout	<input type="checkbox"/>	<input checked="" type="checkbox"/>
530	feet to	545	hole plug	<input type="checkbox"/>	<input checked="" type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments  
clean well out from 380' to 545'

Neat Cement Fluid Weight \_\_\_\_\_ lbs/gal  
 Bentonite Grout \_\_\_\_\_ % bentonite

This was an open bore hole

Date Started 9/21/2009  
 Date Completed 9/22/2009

39.497799°N  
 119.613754°W  
 N45 27 (TA)  
 STATE ENGINEERS OFFICE  
 2009 SEP 28 AM 11:58

9 DRILLER'S CERTIFICATION  
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
 Name McKay Drilling Inc.  
 Address 4850 Joule St #A5  
Reno, NV 89502  
 Nevada contractor's license number 14170  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the 2121  
 Division of Water Resources, the on-site driller  
 Signed Steve McKay  
 By driller performing actual drilling on site or contractor  
 Date 9/25/2009