

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 108866
Permit No. _____
Basin 044

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

65006

NOTICE OF INTENT NO. 77914

1 OWNER Anglo Gold Ashanti
MAILING ADDRESS 460 West Silver St. Suite 106 ELKO, NV 89801

ADDRESS AT WELL LOCATION Big Springs Mine - North Sammy Creek Pit
Subdivision Name: _____ County EKO

2 LOCATION SW 1/4 Sec 2 T 42 S R 53
PERMIT/WAIVER No. 53002

Latitude _____ UTM E 11T0585556 NAD 27
Longitude _____ N 4601752 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NOI? _____

Is there an existing well log? yes
If yes, what is NDWR well log #: 36836 (T4)

4 EXISTING WELL CONSTRUCTION

Depth Drilled 335' Feet Depth Cased 335' Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>8 3/8</u>		<u>188</u>	<u>+2</u>	<u>335</u>

7 WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:
Type of perforation Mill Slot
Size of perforation 3/16 x 3

From	To
<u>96</u> feet to <u>335</u> feet	

If casing was left in place, please show where additional perforations were made:
Additional Perforations: Tim Hunt said - Don't have to Perf.

From	To	Number of perms per linear foot

5 WATER LEVEL
Static water level 208 feet below land surface
Artesian flow NO G.P.M. 125 P.S.I.
Water temperature _____ °F Quality Clean

8 WELL PLUGGING MATERIALS

From	To	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<u>335</u> feet to <u>185</u> feet	<u>Super plug</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<u>185</u> feet to <u>80</u> feet	<u>Super plug</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<u>80</u> feet to <u>20</u> feet	<u>cement</u>	<input type="checkbox"/>	<input type="checkbox"/>	
<u>20</u> feet to <u>0</u> feet	<u>2 1/2" Hole plug cement</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
		<input type="checkbox"/>	<input type="checkbox"/>	

Neat Cement Fluid Weight _____ lbs/gal
Bentonite Grout _____ % bentonite

Date Started 9-27-09
Date Completed 9-29-09

6 Additional Notes or Comments
Blockage at 54' - enter well & cleaned to bottom - trash - soda cans, plastic bottles, bags, metal bands, just a mess.
Blow on well at bottom for 30 min. It's clean. Let set for 2 hrs.
Static is at 208. Pulled pipe & ran trimmer in well - mix & pump 50 bags super plug & 10 bags cement.
pulled trimmer up over night.
Next morning tag up at 185' mix & pump 60 bags super plug & 10 more bags cement. Pulled trimmer & tag up at 30' pull trimmer out. Poured 40 bags 3/4" hole plug 30' up to 20'.
Mix & pump 10 bags cement 20' up to 0' very very good seal.

STATE ENGINEERS OFFICE
41.564704 N
115.973932 W
2009 OCT 5 AM 11:58
NAD 27
(T4)

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Rimrock Drilling Contractor
Address 2305 Last Chance Rd. ELKO NV. 89801 Contractor

Nevada contractor's license number issued by the State Contractor's Board 0030630
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676

Signed Ward Weaver By driller performing actual drilling on-site or contractor
Date 10-1-09

USE ADDITIONAL SHEETS IF NECESSARY