WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

MW-20

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 109267
Permit No.
Basin 090

NOTICE OF INTENT NO. 65104

1. OWNER TOM BAUHS on Behalf of Chevron
MAILING ADDRESS P.O. Box 6012
San Ramon, CA. 94583

ADDRESS AT WELL LOCATION 948 Enoline Way
Incline Village, NV.

2. LOCATION NW 1/4 SE 1/4 Sec. 15 T. 16 N S R. 18 E. WASHOE County
PERMIT NO. Issued by Water Resources | Parcel No. 127-030-15 | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Sonic

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	5	5
Gravelly Silt		5	10	5
No Recovery		10	12	2
Varying Sand		12	14.5	2.5
Clay		14.5	17	2.5
Gravelly Silt		17	20	3
Sand		20	27	7
Sandy Clay		27	29	2
Sand		29	31	2
No Recovery		31	32	1
Clay		32	35.5	3.5
Sand		35.5	37	1.5
Clayey Sand		37	38.5	1.5
Gravelly Sand		38.5	40	1.5
No Recovery	40.35	40	42	2
Silty Sand		42	48	6
Sand		48	52	4
Clay		52	53	1

39.248224°N
119.945892°W
NAD 27 (TA)

Date started 10/17, 2009
Date completed 10/26, 2009

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 53 Feet Depth Cased 50 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
6.5	0	53

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	0	50

Perforations:
Type perforation SLOT
Size perforation 0.020
From 20 feet to 50 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 17
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 53 feet to 17 feet

9. WATER LEVEL
Static water level 40.35 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality NA

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Boart Longyear Contractor
Address 1333 W. 9th St. Contractor
Upland, CA. 91786
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2405
Signed [signature] By driller performing actual drilling on site or contractor
Date 11/21/09

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627