WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 109925
Permit No.
Basin 084

NOTICE OF INTENT NO. 50440

1. OWNER THE BOING COMPANY
MAILING ADDRESS 6633 Canoga Avenue D-393 T-487
CAnoga Park, CA 91303

ADDRESS AT WELL LOCATION Rocketdyne, NV Field Laboratory, Washoe County, Nevada
800 Axe Handle Canyon Road, Reno, NV 89510

2. LOCATION NE ¼ SW ¼ Sec. 28 T 22N N/S R 21 E Washoe County
PERMIT NO. Affid.3-25-03/B-21A (Issued by Water Resources) 076-150-01 (Parcel No.) Area B Palomino Valley (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☒ Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
GRANODIORITE		0	71.6	71.6
greyish orange, fine				
to medium granied,				
abundante biotite,				
intensly weathered				
slightly weathered		@10		
medium dark grey				
fracture		@36		
frature		38	41	3
Soft zone, possible				
production of 1 GPM	X			
fracture making water	X	@49		
fracture		@52		
fracture		@55		
soft and weathered		56	57	1
fracture		@60		
increase in water				
production	X	@64		
from 1 GPM to 5 GPM				
Total depth of borehole 71.6 feet				

Date started April 15, 2003, 20
Date complated April 16, 2003, 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			
Information recieved 12-04 06			

8. WELL CONSTRUCTION
Depth Drilled 71.6 Feet Depth Cased 71.6 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
9 Inches		0 Feet	71.6 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"	sch 40	PVC casing	0	71.6
4" end	cap.4"	security cap.	4" stainless steel	
centralizers @26.1'. 8" locking monument				

Perforations:
Type perforation factory sawed slot
Size perforation 0.020"slots
From 21.1 feet to 71.6 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 15.9
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Bentonite seal: 15.9 - 17.9 ft.
Gravel Packed: ☒ Yes ☐ No SRI #8 sand
From 17.9 feet to 71.6 feet

9. WATER LEVEL
Static water level 30.5 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality not known

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed (By driller performing actual drilling on site or contractor)
Date December 4, 2006

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627