

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37102

CONSULTANT: CDM Engineers & Constructors CLIENT: ADDRESS AT WELL LOCATION Sparks Solvent/Fuel Site
1. OWNER: 50 W. Liberty, Suite 770 Vista Canyon Group/Sparks Terminal property and
MAILING ADDRESS: Reno, NV 89501 Union Pacific RR property
2. LOCATION: NW 1/4 NW 1/4 Sec 10 T 19N N/S R 20 E Washoe County
PERMIT NO. Well# MW-226 037-030-09 Sparks, NV
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED 4. PROPOSED USE 5. WELL TYPE
 New Well Replace Recondition Domestic Irrigation Test Cable Rotary RVC
 Deepen Abandon Other _____ Municipal/Industrial Monitor Stock Air Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Dry, loose, brown SILT, little sand, trace gravel.		0	12	12
Medium dense, gray brown, c m f GRAVEL, and c m f SAND, little silt.		12	43	31
@20' Trace silt @35' Color change to brown				
Wet, medium, dense, brown, c m f GRAVEL and c m f SAND little slit.		43	49	6
Wet, medium, dense, brown gray, c m f GRAVEL and c m f SAND little silt		49	54	5
Wet, medium, dense, brown gray, c m f GRAVEL and c m f SAND little silt		54	57.8	3.8

8. WELL CONSTRUCTION
Depth Drilled 57.8 Feet Depth Cased 57.8 Feet
HOLE DIAMETER (BIT SIZE)
From 8 5/8 Inches To 0 Feet 57.8 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" SCH 40 PVC			2	12
Locking Well Cap				
Threaded PVC End Cap				

Perforations:
Type perforation Factory Sawn Slot
Size perforation 0.06
From 25 feet to 56.8 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: Yes No Seal Type:
Depth of Seal 8 Neat Cement
Placement Method: Pumped Cement Grout
 Poured Concrete Grout
Bentonite Seal at: 8.1-10 Lonestar coarse
Gravel Packed: Yes No Aquarium sand
From 35 feet to 58.6 feet

9. WATER LEVEL
Static water level 15 feet below land surface
Artesian flow _____ G.P.M. _____ P.S.I.
Water temperature _____ °F Quality NOT KNOWN

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Wayne Drilling Inc. Contractor
Address P.O. Box 12370 Contractor
Reno, NV 89510

Nevada contractor's license number issued by the State Contractor's Board 22549

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908

Signed *Wayne Drilling Inc.*
By Driller performing actual drilling on site or contractor
Date January 20, 2003

Date started 11-10-97, 20
Date completed 11-13-97, 20

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No test			