

Log No. 10968  
Permit No. 087  
Basin 087

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37113

Consultant: CDM Engineers & Construction  
1. OWNER: 50 West Liberty St. Suite 770  
MAILING ADDRESS: Reno, N.V. 89502

Client: Vista Canyon Group  
ADDRESS AT WELL LOCATION: Sparks solvent fuel site  
Sparks, N.V.

2. LOCATION: NE 1/4 NE 1/4 Sec. 9 T. 19 N. N/S R. 20 E Washoe County  
PERMIT NO. MW-210A 034-102-14  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other  
4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other LUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Dry, loose, brown, SILT, trace gravel		0.00	5.00	5.00
As Above, little gravel below 5 feet water added during drilling below 5 feet		5.00	7.00	2.00
Medium dense, gray brown, cmf GRAVEL little sand and silt		7.00	20.00	13.00
As Above, wet below 20 feet		20.00	25.00	5.00
As Above, color change to brown gray below 25 feet moderate		25.00	28.00	3.00
As Above, color change to brown		28.00	30.00	2.00

8. WELL CONSTRUCTION  
Depth Drilled 30 Feet Depth Cased 27.45 Feet  
HOLE DIAMETER (BIT SIZE)  
From To  
8" 5/8 Inches 0 Feet 30 Feet  
Inches Feet Feet  
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"	W/Cap	SCH.40 PVC	0	7
12 in. Dia. Steel Threaded PVC Endcap				

Perforations:  
Type perforation: Factory Sawn Slot  
Size perforation: 0.06 in. Slot Screen  
From 7 feet to 27.45 feet  
From feet to feet  
From feet to feet  
From feet to feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  
Depth of Seal: 0-2.7 Ft.  Cement Grout  
Placement Method:  Pumped  Concrete Grout  
 Poured  
Bentonite Seal At: 2.7 Ft.-4.9  
Gravel Packed:  Yes  No Coarse Aquarium  
From 4.9 feet to 30 feet

9. WATER LEVEL  
Static water level: not known feet below land surface  
Artesian flow: G.P.M. n/a P.S.I.  
Water temperature: n/a °F Quality: n/a

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name: Wayne Drilling Inc. Contractor  
Address: P.O. Box 12370 Contractor  
Reno, N.V. 89510  
Nevada contractor's license number issued by the State Contractor's Board: 0022549  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 908  
Signed: *Wayne Drilling Inc.*  
By driller performing actual drilling on site or contractor  
Date: September 5, 2000

Date started: 11-03-97 19  
Date completed: 11-04-97 19

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No Test			