

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

**WELL DRILLER'S REPORT**

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 50413

1. Consultant: HALEY AND ALDRICH, INC. Client: ADDRESS AT WELL LOCATION THE B OEING CO.  
 MAILING ADDRESS 6200 East 14th St., Suite A200 6633 Canoga Avenue, D/393 T/487  
Tucson, Arizona 85711 Canoga Park, California 91303  
 2. LOCATION SW 1/4 SW 1/4 Sec. 12 T. 22N N/S R. 21 E. Washoe County  
 PERMIT NO. Well D-54A 77-110-22 Area D Whiskey Springs Road  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sand & gravel, grayish brown, medium to coarse sand, fine & coarse gravel, sub-angular, well graded, loose. Mixed rhyolite fragments		0	15	15
Silty sand & gravel, grayish brown, fine to coarse sand, well graded, loose		15	71 1/2	56 1/2
Tuff, abundant quartz bipyramids, some chatoyant feldspar, moderately welded.				
Tuff of Chimney Springs		71 1/2	74.4	2.9
Drilled through boulder from 36-39 ft. Weathered bedrock from approx 65-72 ft.				

8. WELL CONSTRUCTION  
 Depth Drilled 74.4 Feet Depth Cased 74.4 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 9 5/16 Inches To 0 Feet 74.4 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		sch 40	+2.03	39.4
4" PVC box cap,		stainless steel centralizers,		
4" PVC security cap,		8"x5" locking monument		

Perforations:  
 Type perforation Factory sawed slot  
 Size perforation 0.020  
 From 39.4 feet to 74.4 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 0-32.5 ft  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Bentonite seal: 32.5 - 34 ft.  
 Gravel Packed:  Yes  No SRI#3 sand  
 From 34 feet to 74.4 feet

9. WATER LEVEL  
 Static water level 47.6 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality not known

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC.  
 Contractor  
 Address P.O. BOX 12370  
 Contractor  
RENO, NEVADA 89510

Nevada contractor's license number 0022549  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the 908  
 Division of Water Resources, the on-site driller  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date August 11, 2002

Date started 7-12-2002, 20  
 Date completed 7-15-2002, 20

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No test			