

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No. _____
 Permit No. _____
 Basin 024

NOTICE OF INTENT NO. 50412

1. Consultant: HALEY AND ALDRICH, INC. Client: _____
 OWNER _____ ADDRESS AT WELL LOCATION: THE BOEING CO.
 MAILING ADDRESS: 6200 East 14th St., Suite A200 6633 Canoga Avenue, D/393 T/487
Tucson, Arizona 85711 Canoga Park, California 91303
 2. LOCATION: SW 1/4 SW 1/4 Sec. 12 T. 22N N/S R. 21 E Washoe County
 PERMIT NO. Well D-55A 77-110-22 Area D, Whiskey Springs Road
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sand with gravel, moderate brown, fine to coarse sand, fine to coarse gravel, subangular, loose well graded		0	10	10
Silty sand with gravel, grayish brown, fine to coarse sand, well graded, loose		10	15	5
Sandy clay with gravel, grayish brown, fine to coarse sand, fine to coarse gravel, subangular, well graded		15	30	15
Silty sand with gravel, grayish brown, fine to coarse sand, well graded, loose		30	62 1/2	32 1/2
Tuff, moderately red, poorly to moderately welded, abundant smokey quartz bipyramids, occasional feldspar phenocrysts, tuff of chimney Spring.		62 1/2	68.6	6.1

8. WELL CONSTRUCTION
 Depth Drilled 68.6 Feet Depth Cased 68.6 Feet
 HOLE DIAMETER (BIT SIZE)
 From 9 5/16 Inches To 0 Feet 68.6 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC		sch 40	+1.9	38.6
4" PVC	box cap	stainless steel centralizers,		
4" PVC	security cap,	8" x 4" locking monument		

 Perforations: factory sawed slot
 Type perforation _____
 Size perforation 0.020
 From 38.6 feet to 68.6 feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type:
 Depth of Seal 0 - 32.6 ft Neat Cement
 Cement Grout
 Placement Method: Pumped Concrete Grout
 Poured
 Bentonite seal: 32.6 - 34.8 ft SRI # sand
 Gravel Packed: Yes No
 From 34.8 feet to 68.6 feet

9. WATER LEVEL
 Static water level 66.1 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality Not known

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number 0022549
 issued by the State Contractor's Board.
 Nevada driller's license number issued by the 908
 Division of Water Resources, the on-site driller.
 Signed [Signature]
 Driller performing actual drilling on site or contractor
 Date August 11, 2002

Date started 7-10-2002, 19_____
 Date completed 7-11-2002, 19_____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			