WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 109974
Permit No.
Basin Ø 84

NOTICE OF INTENT NO. 50431

1. ~~OWNER~~ Consultant: HALEY AND ALDRICH, INC.
MAILING ADDRESS 6200 East 14th St., Suite A200
Tucson, Arizona 85711

Client:
ADDRESS AT WELL LOCATION THE BOEING CO.
6633 Canoga Avenue,D/393 T487
Canoga Park, CA 91303

2. LOCATION NE ¼ SE ¼ Sec. 18 T. 22N N/S R. 22 E. Washoe County
PERMIT NO. R-422A Well C-20A (Issued by Water Resources) 77-310-04 (Parcel No.) Area C, 2700 Right Hand Canyon Road (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand with silt, light brown, fine sand, small percentage of fine gravel, poorly graded, moist, some clay		0	20	20
Sand, light brown, fine to medium sand, poorly graded, moist, some silt		20	24	4
Tuff, moderately welded, red-brown and olive fragments in cuttings		24	29.2	
Chugach Well Log No. 116281				

Date started 11-19-2002, 20
Date completed 11-20-2002, 20

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			

8. WELL CONSTRUCTION
Depth Drilled 29.2 Feet Depth Cased 29.2 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
11½ Inches		0 Feet	29.2 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5 3/4"	PVC	sch 80	+1.91	9.2
PVC end cap, compression cap, centralizers				
8"x5' locking monument				

Perforations:
Type perforation factory sawed slot
Size perforation 0.020
From 9.2 feet to 29.2 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 0-5.4 ft
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout
Bentonite seal; 5.4-7 ft
Gravel Packed: [X] Yes [ ] No SRI #8 sand
From 7 feet to 29.2 feet

9. WATER LEVEL
Static water level Dry feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality Not known

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date December 10, 2002

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627