

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 11979
 Rec. 19
 Well No. 25399
 Permit No. 25399
Do not fill in

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Basin #108

Owner THE ANACONDA COMPANY Driller THE ANACONDA COMPANY
 Address Weed Heights, Nevada 89443 Address Weed Heights, Nev. 89443 Lic. No.
 Location of well: SE 1/4 SE 1/4 Sec. 16, T13 N R. 25 E, in County
 or
 Water will be used for Milling, Mining, Domestic Total depth of well 300'
 Size of drilled hole 20" φ Weight of casing per linear foot 18" - 47 lbs.
 Thickness of casing 1/4" Temp. of water 62°
 Diameter and length of casing 20" to 178', 18" to 300'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 60'
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well February 1, 1969 Date of completion of well April 15, 1969
 Type of well rig Bucyrus-Erie 42 T. Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	60	60	Gravel
60	300	240	Porphyry

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 60 to 300 ft.

Other aquifers

First water at 60 feet.

Casing perforated
 from 100 to 300 ft.

Size of perforations
1/4" x 10"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	Remarks—Seals, Grouting, Etc.
20"	0	178	178	15 cu. yds. pea gravel around top of casing.
18"	0	300	300	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No.....

Dated....., 19.....

(Not to be filled in by Driller)
