ORIGINAL

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 110114
Permit No.
Basin 108

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64150

1 OWNER Mason Valley Wildlife Management Area
MAILING ADDRESS One Lux Lane
Yerington, NV 89447

ADDRESS AT WELL LOCATION Mason Valley
N. Bybee Lane
Subdivision Name: County: Lyon

2 LOCATION NW ¼ SE ¼ Sec 3 T 14 N/S R 26 E
PERMIT/WAIVER No. 17660 Issued by Water Resources Parcel No.

Latitude 39* 06.246 N
Longitude 119* 03.365 W
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3 TYPE OF WELL
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #? 4750

4 *EXISTING WELL CONSTRUCTION*
Depth Drilled 160' Feet Depth Cased 123' Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12"		.188"	0'	123'

Existing Perforations:
Type of perforation MILL SLOT
Size of perforation 3/16" X 8"

From	87'	feet to	123'	feet
From		feet to		feet
From		feet to		feet
From		feet to		feet
From		feet to		feet

5 *WATER LEVEL*
Static water level 12' feet below land surface
Artesian flow G.P.M. P.S.I
Water temperature °F Quality

6 Additional Notes or Comments

39.104181°N
119.055097°W
NAD 27 (TN)

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☒ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☐ yes ☒ no
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:

Additional Perforations:
Type of perforater used: Holt Air Perforator

From	0'	feet to	90'	feet	Number of perfs per linear foot	8 rows
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	

8 WELL PLUGGING MATERIALS

					Material Used		
From	0'	feet to	20'	feet	NEAT CEMENT	☒ Pumped	☐ Poured
From	20'	feet to	123'	feet	GOPHER GROUT	☒ Pumped	☐ Poured
From		feet to		feet		☐ Pumped	☐ Poured
From		feet to		feet		☐ Pumped	☐ Poured
From		feet to		feet		☐ Pumped	☐ Poured
From		feet to		feet		☐ Pumped	☐ Poured

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 20% % bentonite
Date Started 1/13/2010
Date Completed 2/5/2010

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources Nevada Inc dba Humboldt Drilling & Pump Co (Contractor)
Address 4975 W. Winnemucca Blvd. (Contractor)
Winnemucca, Nevada 89445
Nevada contractor's license number issued by the *State Contractor's Board* 56797
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* # 2355
Signed Cheryl Jaques Office (By driller performing actual drilling on site or contractor)
Date 2/12/2010

(Rev. 05-09)

USE ADDITIONAL SHEETS IF NECESSARY