STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY

Log No. 110369

Permit No.

Basin 179

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64537

1. OWNER Robinson NV. Mining PZ09-08

MAILING ADDRESS PO Box 382

Ruth, NV. 89319

ADDRESS AT WELL LOCATION Ruth, NV.

Subdivision Name: County: White Pine

2. LOCATION SW¼NE¼ Sec14T16N/ R62E

PERMIT/WAIVER NO. m/o - 1605

Issued by Water Resources Parcel. No.

Latitude 39.25408°N UTM E 676090 ☒ NAD 27

Longitude 114.959255°W N 4346749 ☐ NAD 83/WGS 84

NAD 27 AB

3. WORK PERFORMED

☒ New Well ☐ Replace ☐ Recondition

☐ Deepen ☐ Other

4. PROPOSED USE

☐ Domestic ☐ Irrigation ☐ Test

☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE

☐ Cable ☐ Rotary ☒ RVC

☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Yellow Limestone		0	140	140
Gray Limestone		140	240	100
White Limestone		240	280	40
Orange Limestone		280	340	60
Gray Limestone		340	360	20
Orange Clay		360	400	40
White Limestone		400	460	60
Gray Limestone		460	480	20
White Limestone		480	520	40
Dark Gray Limestone		520	540	20
White Clay		540	560	20
Orange Limestone		560	580	20
Gray Limestone		580	660	80
Gray/Green Limestone		660	800	140
White Skarn		800	850	50
Gray /Green Limestone		850	875	25
Transducers at 870', 770', 670'				
.750 PVC Cemented inside & out.				

Date started: November 12, 20 09

Date completed: November 18, 20 09

9. WELL CONSTRUCTION

Depth Drilled 875 Feet Depth Cased 875 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12.75 Inches	0 Feet	20 Feet
6.50 Inches	20 Feet	875 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7.75	23.54	.301	1.50	20
.75	.28	.154	0	875

Perforations: N/A

Type of perforation

Size of perforation

From feet to feet

From feet to feet

From feet to feet

From feet to feet

From feet to feet

Annular Seal: ☒ Yes ☐ No

☒ Neat Cement 0 to 50 ☐ Pumped ☒ Poured

☐ Cement Grout to ☐ Pumped ☐ Poured

☐ Concrete Grout to ☐ Pumped ☐ Poured

☒ =30% Bentonite Grout 60 to 875 ☒ Pumped ☐ Poured

Gravel Pack: ☐ Yes ☒ No to ☐ Pumped ☐ Poured

Type:

Bentonite Chips: ☒ Yes ☐ No 50 to 60 ☐ Pumped ☒ Poured

Type: 3/8 Hole Plug

7. Water Level

Static water level: 540 feet below land surface

Artesian Flow: G.P.M. P.S.I

Water Temperature: °F

Quality:

8. WELL TEST DATA

TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Boart Longyear (CONTRACTOR)

Address 2745 California Ave. (CONTRACTOR)

SLC., UT. 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2308

Signed [signature]

By driller performing actual drilling on site or contractor

Date March 5, 2010