

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY

Log No. 110406
Permit No. 71
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62744

1. OWNER Donn & Sue Sakurada ADDRESS AT WELL LOCATION 7140 Jackson
MAILING ADDRESS 7140 Jackson Winnemucca, Nv 89445 Subdivision Name: Winnemucca, Nv 89445 County: Humboldt
2. LOCATION NW 1/4 NW 1/4 Sec 18 T 35N N/S R 37E E Latitude 40 54.781n UTM E NAD 27
PERMIT/AWAIVER No. 13-541-16 Longitude 117 45.815w N 110406
Issued by Water Resources Parcel No.

3. WORKED PERFORMED
New Well Replace Recondition
Deepen Other
4. PROPOSED USE
 Domestic Irrigation Test
Municipal/Industrial Monitor Stock
5. WELL TYPE
Cable RVC
Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sandy loam top soil		0	5	5
Med gravel clay & sand		5	10	5
Sand, small gravel & cobbles		10	80	70
Sand, med gravel & cobbles		80	200	120
Sand small gravel & clay		200		-200

9. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200
HOLE DIAMETER (BIT SIZE)
10 7/8 inches From 0 Feet To 200 Feet
 inches From Feet Feet
 inches From Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.376	STEEL	.188	0	20
6.900	PVC	sdr21=.450 in	20	200

Perforations:
Type of perforation 6 inch pvc mill horizontal slot screen
Size of perforation 1/32
From 160 feet to 200 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: Yes
Neat Cement to Pumped Poured
Cement Grout 4 to 52 Pumped Poured
Concrete Grout to Pumped Poured
≥30% Bentonite Grout to Pumped Poured
Gravel Pack: Yes No 54 to 200 Pumped Poured
Type: 3/8 minus
Bentonite Chips: Yes No 52 to 54 Pumped Poured
Type: 3/8 baroid

Date started: 7/20/2008
Date completed: 7/22/2008

7. Water Level
Static water level: 128 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: COLD °F
Quality:

8. WELL TEST DATA

TEST METHOD:	Boiler	Pump	Air Lift	x
	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	
AIR	55	50	4	

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name High Desert Drilling LLC
Contractor
Address 4225 E Mary Way
Contractor
Winnemucca Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board 6222
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 214
Signed # 2301
By driller performing actual drilling on-site or contractor
Date 3-23-2010

STATE ENGINEER RECEIVED
2010 MAR 29 AM 11:28

USE ADDITIONAL SHEETS IF NECESSARY

40.913096° N
117.762620° W
NAD 27 (TN)