STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 110410
Permit No.
Basin 070

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 24147

1. OWNER Dan Debord
MAILING ADDRESS 5645 Blue Heron RD
Winnemucca, Nv

ADDRESS AT WELL LOCATION 5645 Blue Heron RD
Winnemucca, Nv
Subdivision Name: JB Estates Development County: Humboldt

2. LOCATION SE ¼ SE ¼ Sec 2 T 35N N/S R 37E E
PERMIT/WAIVER No. 0 13-037-01
Issued by Water Resources Parcel No.

Latitude 40 55.913N
Longitude 117 46.634W
UTM E
N
[X] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well Replace Recondition
Deepen Other

4. PROPOSED USE
[X] Domestic Irrigation Test
Municipal/Industrial Monitor Stock

5. WELL TYPE
Cable [X] Rotary RVC
Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
clay & silt		0	75	75
gravel & sand		75	85	10
clay & silt		85	95	10
gravel with clay and sand stratas		95	120	25
clay & silt		120	135	15
gravel & sand		135	145	10
clay & silt		145	150	5
gravel & sand		150	185	35
clay & silt		185	205	20
		205	220	15
				220

Date started: 5-23, 20 07
Date completed: 5-26, 20 07

9. WELL CONSTRUCTION
Depth Drilled 220 Feet Depth Cased 220

HOLE DIAMETER (BIT SIZE)

		From	To
10 5/8	Inches	0 Feet	220 Feet
	Inches	Feet	Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.5	STEEL	.188	0	20
6.75	pvc	sdr21	20	220

Perforations:
Type of perforation PVC Screen
Size of perforation 3/16
From 180 feet to 220 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: Yes

Neat Cement	to		Pumped	Poured
Cement Grout	0 to 80		Pumped	[X] Poured
Concrete Grout	to		Pumped	Poured
≥30% Bentonite Grout	to		Pumped	Poured

Gravel Pack: [X] Yes No 80 to 220 Pumped [X] Poured
Type: 3/8 minus
Bentonite Chips: [X] Yes No to Pumped [X] Poured
Type: 3/8 baroid

7. Water Level
Static water level: 78 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cool °F
Quality: good

8. WELL TEST DATA
TEST METHOD: Bailer Pump Air Lift x

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
35		4

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Contractor High Desert Drilling LLC
Address Contractor 4225 E Mary Way
Winnemucca Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board 62237
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2740
Signed By driller performing actual drilling on site of contractor
Date 3-23-2010

RECEIVED
2010 MAR 29 AM 11:22
STATE ENGINEER'S OFFICE

(Rev. 05-06) USE ADDITIONAL SHEETS IF NECESSARY

410.931900°N
117.776269°W
Nad 27 TW