

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 63151 (1)

1. OWNER Richard Andrews ADDRESS AT WELL LOCATION \_\_\_\_\_  
 MAILING ADDRESS 3150 Potbelly Rd. Winnemucca NV. 89445 \_\_\_\_\_  
 2. LOCATION SE 1/4 NE 1/4 Sec 25 T 35 R 37 E Humboldt County \_\_\_\_\_  
 PERMIT NO. 014-143-10 Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>Sandy Gravel</u>	<u>XCS</u>	<u>133</u>	<u>230</u>	<u>97</u>
<u>N40°54'780</u>				
<u>W117°45'873</u>				
<u>NA0 27</u>				
<u>N40°52'974</u>				
<u>W117°45'569</u>				
<u>883°N NA027 D.D.</u>				
<u>117.759°W</u>				

8. WELL CONSTRUCTION  
 Depth Drilled 133 to 230 Depth Cased 130 to 230 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 6 Inches 133 Feet To 230 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>4.25</u>	<u>Sched 40</u>	<u>PVC</u>	<u>120</u>	<u>230</u>

Perforations:  
 Type perforation Hand Cut  
 Size perforation .25  
 From 140 feet to 230 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal NA  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No  
 From 130 feet to 230 feet

Date started 5-29, 2009  
 Date completed 5-28, 2009

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>20</u>	<u>NA</u>	<u>4 hrs.</u>

9. WATER LEVEL  
 Static water level 110' feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature cool °F Quality clear

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Firstgold Corp. P.O. Box Contractor  
 Address P.O. Box 6 Contractor  
Lovelock NV. 89419  
 Nevada contractor's license number issued by the State Contractor's Board 0071020  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 730  
 Signed Frank Monty  
 By driller performing actual drilling on site or contractor  
 Date 5-8-09