STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 110546
Permit No.
Basin 101

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 63723

1. OWNER Ken Hendrix
MAILING ADDRESS 5741 Indigo Run Drive
Reno, NV 89511

ADDRESS AT WELL LOCATION 2452 Harvey Lane
Fallon, NV 89406
Subdivision Name: County: Churchill

2. LOCATION SE¼SW¼ Sec15T19N/ R28E
PERMIT/WAIVER NO. 008-081-21
Issued by Water Resources Parcel. No.

Latitude 39.50684 UTM E ☐ NAD 27
Longitude -118.82979 N ☒ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Brown Sand		0	3	3
Brown Clay		3	18	15
Brown Sand		18	37	19
Green Clay		37	39	2
Pea Gravel		39	42	3
Black Sand		42	75	33
Black Sand		75	87	12
Brown Pea Gravel		87	106	19
Brown Sand		106	137	31
Green Clay		137	144	7
Black Clay		144	146	2
Green Pea Gravel		146	158	12
Brown Clay		158	164	6
Brown Sand		164	173	9
Brown Gravel	X	173	180	7

39.506,9223°N NAD27 D.D.
118.828,802°W

Date started: 3/12, 20 09
Date completed: 3/13, 20 09

7. Water Level
Static water level: 30 feet below land surface
Artesian Flow: G.P.M. P.S.I
Water Temperature: cool °F
Quality: Unknown

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
15		1hr

9. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12.25 Inches	0 Feet	50 Feet
10 Inches	50 Feet	180 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	12.92	.188	0	20
6.625PVC	4.1	.316	20	180

Perforations:
Type of perforation Saw Cut
Size of perforation 1/8
From 176 feet to 180 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 10 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☒ ≥30% Bentonite Grout 10 to 50 ☒ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 180 to 50 ☐ Pumped ☒ Poured
Type: 3/8
Bentonite Chips: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Parsons Drilling,Inc. (CONTRACTOR)
Address P.O. box 1265 (CONTRACTOR)
Fallon, NV 89407-1265
Nevada contractor's license number issued by the State Contractor's Board 29064
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2307
Signed
By driller performing actual drilling on site or contractor
Date 3/27/2009

(Rev 05-06) USE ADDITIONAL SHEETS IF NECESSARY

Forms Provided by Forms-On-A-Disk · (214) 340-9429 · FormsOnADisk.com