

FINALIZED M&M

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 110613
Permit No.
Basin 101

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62682

1. OWNER Julie King
MAILING ADDRESS P.O. Box 867
Fallon, NV 89406
ADDRESS AT WELL LOCATION 9170 Allen Road
Fallon, NV 89406
Subdivision Name:
County: churchill

2. LOCATION SE 1/4 NW 1/4 Sec 12 T17 N N/S R28E
Latitude 39.35325N UTM E NAD 27
PERMIT/WAIVER NO. 006-031-52 Longitude 118.79403W N NAD 83/WGS 84
Issued by Water Resources Parcel No.

3. TYPE OF WELL
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock
Is this well being plugged because a replacement well was drilled? [X] Yes [ ] No
If yes, what is replacement well NOI? 60029
Is there an existing well log? [X] Yes [ ] No
If yes, what is NDWR well log #? 43773

4. EXISTING WELL CONSTRUCTION
Depth Drilled 20 Feet Depth Cased 20 Feet

Table with 5 columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet). Row 1: 6, 12.92, .188, 0, 20.

Existing Perforations:
Type of perforation well screen
Size of perforation .020
From 15 feet to 20 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

5. WATER LEVEL
Static water level: 9 feet below land surface
Artesian flow: G.P.M. P.S.I.
Water Temperature: cool °F Quality unknown

6. Additional Notes or Comments
Cement was pumped from bottom to top of well
Pumped 6 bags of cement

GPS NAD-27
39.353331°N
118.793046°W

2008 SEP 26 11:07 AM
STATE ENGINEER

7. WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? [X] Yes [ ] No
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? [ ] Yes [X] No
Was the casing pulled? [ ] Yes [X] No
Was the casing over drilled? [ ] Yes [X] No
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used:
From feet to feet Number of perfs per linear foot

8. WELL PLUGGING MATERIALS

Table with 4 columns: From, feet to, feet, Material Used. Rows for Cement (Pumped/Poured) and Neat Cement Fluid Weight (15.6 lbs/gal).

Neat Cement Fluid Weight 15.6 lbs/gal
Bentonite Grout % bentonite

Date Started 9/23/2008
Date Completed 09/23/2008

9. DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Parsons Drilling, Inc (CONTRACTOR)
Address P.O. box 1265 (CONTRACTOR)
Fallon, NV 89407-1265
Nevada contractor's license number issued by the State Contractor's Board 29064
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2307

Signed [Signature]
By driller performing actual drilling on site or contractor
Date 09/24/2008