

FINALIZED MH  
PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 63149

1. OWNER Sheldon Rehberg ADDRESS AT WELL LOCATION \_\_\_\_\_  
MAILING ADDRESS 13913 S. Grass Valley Rd. Winnemucca NV. 89445 13913 S. Grass Valley Rd. Winnemucca NV. 89445  
2. LOCATION SW 1/4 SW 1/4 Sec. 17 T. 34 N. R. 38 E. Narsching County \_\_\_\_\_  
PERMIT NO. NA Parcel No. 009-240-06 Subdivision Name NA  
Issued by Water Resources \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
<u>Sand, boulders</u>	<u>NO</u>	<u>0</u>	<u>50</u>	
<u>Rock Sand Gravel</u>	<u>NO</u>	<u>100</u>	<u>190</u>	
<u>Clay, Rock</u>	<u>NO</u>	<u>190</u>	<u>240</u>	
<u>Cemented Rock, clay</u>	<u>NO</u>	<u>240</u>	<u>260</u>	
<u>Rock, cemented rock</u>	<u>NO</u>	<u>260</u>	<u>300</u>	
<u>Rock, Clay</u>	<u>NO</u>	<u>300</u>	<u>340</u>	
<u>Cemented Rock, Clay</u>	<u>Yes</u>	<u>340</u>	<u>400</u>	

NAD-27 GPS  
40° 815' 44.5" N  
117° 7' 33.188" W

8. WELL CONSTRUCTION  
Depth Drilled 400 Feet Depth Cased 400 Feet  
HOLE DIAMETER (BIT SIZE)  
From 10 5/8 Inches To 100 Feet  
From 8 3/4 Inches To 400 Feet  
Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6 5/8</u>	<u>STEEL</u>	<u>.188</u>	<u>0</u>	<u>10</u>
<u>6 3/8</u>	<u>PVC</u>	<u>F480</u>	<u>10</u>	<u>400</u>

Perforations:  
Type perforation Need Cut  
Size perforation .25  
From 340 feet to 400 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
Depth of Seal 50'  Neat Cement  
Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No  
From 50' feet to 400 feet

Date started 11-1-08 20 \_\_\_\_\_  
Date completed 11-19-08 20 \_\_\_\_\_

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>30</u>	<u>N/A</u>	<u>10</u>

RECEIVED  
NOV 25 AM 10:59  
2008

9. WATER LEVEL  
Static water level 280 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature cool °F Quality clear

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Firstgold Corp. Contractor  
Address P.O. Box 6 Lovelock NV. 89419 Contractor  
Nevada contractor's license number 0071020 issued by the State Contractor's Board.  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 0730  
Signed [Signature] By driller performing actual drilling on site or contractor  
Date 11-19-08