Plugging of Well
Log 7196

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 11065!
Permit No. 17102
Basin 030A

NOTICE OF INTENT NO. #64417 (i)

1 OWNER Kings River Ranch
MAILING ADDRESS 129 Kings River Rd.
Orovada, NV. 89425

ADDRESS AT WELL LOCATION Kings River Ranch
129 Kings River Rd Orovada, NV 89425
Subdivision Name: A-6-A County: Humboldt

2 LOCATION SW ¼ NW ¼ Sec 25 T 46 N/S R 33 E
PERMIT/WAIVER No. # 17102 Issued by Water Resources Parcel No.

Latitude N 41° 50' 34.9" UTM E
Longitude W 118° 13' 18.4" N
☐ NAD 27 ☒ NAD 83/WGS 84

3 TYPE OF WELL
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? NO
If yes, what is replacement well NO!?

Is there an existing well log? yes
If yes, what is NDWR well log #? ~~UNKNOWN~~ 7196

4 EXISTING WELL CONSTRUCTION
Depth Drilled Feet Depth Cased Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16		.250	0	300
14		.250	280	400

Existing Perforations:
Type of perforation SAW SLOT
Size of perforation 1/4 x 2

16 From 200 feet to 300 feet
From feet to feet
14 From 280 feet to 400 feet
From feet to feet
From feet to feet

5 WATER LEVEL
Static water level [redacted] 205 feet below land surface
Artesian flow NO G.P.M. P.S.I
Water temperature COOL °F Quality GOOD

6 Additional Notes or Comments

54 - BAGS CEMENT / 7 GALS WATER
50' - 0

12 - BAGS CHIPS - VOLCLAY CHIPS
58' - 50'

580 - BAGS - CRUMBLES - 8/20
58' - 405'

30 GALS POLYMER
4 oz POLYMER / BAG CRUMBLES

WE HAD SEVERAL WEATHER RELATED SHUT DOWNS OTHERWISE WELL PLUGGING UNDERWAY

STATE ENGINEER
2010 MAY 12 AM 11:21

RECEIVED

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☒ yes ☐ no
If well was not cleaned out to total depth, please explain why: THIS WELL WAS BRUSHED AND CLEANED TO BOTTOM BEFORE PLUGGING BEGAN.

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☐ yes ☒ no
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforater used: MILLS KNIFE

From 60 feet to 5 feet Number of perfs per linear foot 4
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot
From feet to feet Number of perfs per linear foot

8 WELL PLUGGING MATERIALS

From	feet to	Material Used	Pumped	Poured
0	50	NEAT CEMENT	☐	☒
			☐	☐
50	405	CRUMBLES	☒	☐
			☐	☐
			☐	☐
			☐	☐

Neat Cement Fluid Weight lbs/gal 12.4 / 12.6
Bentonite Grout CRUMBLES % bentonite 20%
Date Started 2/15/10
Date Completed 4/16/10

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Kings River Ranch (Contractor)
Address 129 Kings River Road (Contractor)
Orovada, Nevada. 89425
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1712
Signed Mike McTinch (By driller performing actual drilling on site or contractor)
Date 5/11/10

USE ADDITIONAL SHEETS IF NECESSARY

NAD-27 GPS = 41.843131°N
118.220788°W

PLD-I
MMH-(F)