STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 110664
Permit No.
Basin 064

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64381

1. OWNER The Estate of Martin T. Wessel c/o Misty Wessel Tour
MAILING ADDRESS 11351 W. Irving Lane
Boise, Id 83713

ADDRESS AT WELL LOCATION Former Ted Chevrons 434 W. Front St
Battle MTN. NV
Subdivision Name: County: Lander

2. LOCATION NW ¼ SW ¼ Sec 17 T 32 N/S R 45 E
PERMIT/WAIVER No #5-000104 002-021-01 002-093
Issued by Water Resources Parcel No.

Latitude N 40.64591°
Longitude W 116.93895°
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other AUGER

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
silt Gravel	NO	0	5	5
silt Sand Gravel	yes	5	10	5
Sand Gravel	yes	10	15	5
Sand	yes	15	20	5
MW-16				
NAD-27 GPS				
40.645998° N				
116.938016° W				

Date started: April 20th, 20 10
Date completed: April 20th, 20 10

9. WELL CONSTRUCTION
Depth Drilled 20 Feet Depth Cased 20 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12	Inches	0	Feet	20	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4		Sch. 40	0	5

Perforations:
Type of perforation Factory Slot
Size of perforation .020
From 5 feet to 20 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 0 to 1 ☐ Pumped ☒ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 3 to 20 ☐ Pumped ☒ Poured
Type: 10/20 silica Sand
Bentonite Chips: ☒ Yes ☐ No 1 to 3 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite Chips

7. Water Level
Static water level: 8 feet below land surface
Artesian Flow: NO G.P.M. P.S.I.
Water Temperature: 65 °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HAZ-Tech Drilling Inc (Contractor)
Address P.O. Box 940 (Contractor)
meridian, Id. 83680
Nevada contractor's license number issued by the *State Contractor's Board* 0038018
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* m-1803T-1
Signed David Gonzales (By driller performing actual drilling on site or contractor)
Date 4/29/10

RECEIVED 2010 MAY -5 AM 11:05 STATE ENGINEER'S OFFICE

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY

MMH (F)