STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 110675
Permit No. 77734
Basin 071

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64153 (i)

1. OWNER Robert Parlasca
MAILING ADDRESS 561 Keystone Avenue, Box 358
TA 9/6/11 SE Reno, Nevada 89503

ADDRESS AT WELL LOCATION 41 miles south of Winnemucca
Bob's Well
Subdivision Name: County: Pershing

2. LOCATION SW ¼ NE ¼ Sec 2 T 32N N/S R 39 E
PERMIT/WAIVER No. 77734
Issued by Water Resources Parcel No.

Latitude N 40' 35.466 UTM E ☐ NAD 27
Longitude W 117' 32.882 N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☒ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
clay and gravel		0	20	
gray basalt		20	560	540
red basalt		560	600	40
gray basalt		600	710	110

RECEIVED
2010 MAY 14 AM 11:23
STATE ENGINEERS OFFICE

NAD-27 GPS
40.591192°N
117.547080°W

Date started: 15-Apr , 20 10
Date completed: 5/2/2010 , 20 10

7. Water Level
Static water level: 460 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cool °F
Quality: good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
3		3

9. WELL CONSTRUCTION
Depth Drilled 700 Feet Depth Cased 700 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 3/4	Inches	0	Feet	710	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625		.250	+2	710

Perforations:
Type of perforation Mill slot
Size of perforation .090 X 3
From 580 feet to 710 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 5 to 105 ☒ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 105 to 710 ☐ Pumped ☒ Poured
Type:
Bentonite Chips: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources Nevada
Contractor
Address 4975 W. Winnemucca Boulevard
Contractor
Winnemucca, Nevada 89445
Nevada contractor's license number issued by the State Contractor's Board 56797
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713
Signed L Tompkins-Admin
by driller performing actual drilling on site or contractor
Date 5/12/2010

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

PLD-I
MMH (F)