

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
 Log No. 11157
 Permit No. 56838
 Basin Ø 51

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65743

1. OWNER **Newmont Mining Corp** LK-71 ADDRESS AT WELL LOCATION **Newmont Gold Quarry**
 MAILING ADDRESS **PO Box 669** **North of Carlin, NV.**
Carlin, NV. 89822 *Subdivision Name:* *County: Eureka*

2. LOCATION **NE¼NE¼ Sec2T33N/ R51E** Latitude _____ UTM E **567416 E** NAD 27
 PERMIT/WAIVER NO. **56838** Longitude _____ N **4514536** NAD 83/WGS 84
Issued by Water Resources Parcel No. _____

3. WORK PERFORMED New Well Replace Recondition
 Deepen Other _____ 4. PROPOSED USE Domestic Irrigation Test
 Municipal/Industrial Monitor Stock 5. WELL TYPE Cable Rotary RVC
 Air Other **Flooded Rev**

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|--|--------------|------|-----|------------|
| Fill - Dump Tailings | | 0 | 220 | 220 |
| Alluvium | | 220 | 550 | 330 |
| Greyish/Green Clay & Siltstone | | 550 | 695 | 145 |
| Tan Siltstone | | 695 | 715 | 20 |
| NAD-27 GPS 40.780946°N 116.201062°W | | | | |
| 2010 JUL - AM 11:17 STATE ENGINEER'S OFFICE | | | | |
| Date started: June 10, 2010 | | | | |
| Date completed: June 20, 2010 | | | | |

9. WELL CONSTRUCTION
 Depth Drilled **715** Feet Depth Cased **700** Feet
 HOLE DIAMETER (BIT SIZE)
 From To
28 Inches **0** Feet **20** Feet
22 Inches **20** Feet **220** Feet
14.75 Inches **220** Feet **715** Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|------------|
| 24 | 109.97 | .437 | 0 | 20 |
| 16 | 42.05 | .250 | 0 | 220 |
| 8.625 | 22.36 | .250 | +2 | 700 |


Perforations:
 Type of perforation **Louvered**
 Size of perforation **.125**
 From **340** feet to **700** feet
 From _____ feet to _____ feet

Annular Seal: Yes No
 Neat Cement 0 to 271 Pumped Poured
 Cement Grout _____ to _____ Pumped Poured
 Concrete Grout _____ to _____ Pumped Poured
 =30% Bentonite Grout _____ to _____ Pumped Poured
 Gravel Pack: Yes No 280 to 715 Pumped Poured
 Type: **1/4"**
 Bentonite Chips: Yes No 271 to 280 Pumped Poured
 Type: **1/2" Coated Kwik Plug**

7. Water Level
 Static water level: **298** feet below land surface
 Artesian Flow: _____ G.P.M. **85** P.S.I.
 Water Temperature: **Cool 52** °F
 Quality: _____

8. WELL TEST DATA

| TEST METHOD: | <input type="checkbox"/> Bailer | <input type="checkbox"/> Pump | <input checked="" type="checkbox"/> Air Lift |
|--------------|---------------------------------|-------------------------------|--|
| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) | |
| 85 | 197.0 | 1 | |
| | OR 495' from Surface. | | |

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name **Boart Longyear** (CONTRACTOR)
 Address **2745 w California Ave** (CONTRACTOR)
SLC, UT. 84104
 Nevada contractor's license number issued by the State Contractor's Board **0021976**
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller **2142**
 Signed 
 By driller performing actual drilling on site or contractor
 Date **June 28, 2010**