

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 6191da  
lower Smoky valley, gutter flats

1. OWNER Sandra Kissell ADDRESS AT WELL LOCATION lower Smoky valley, gutter flats  
 MAILING ADDRESS 1588 Siefert Lane 38° 23.268N 117° 25.934W  
Tenopah, NV 89049 Tenopah, NV  
 2. LOCATION SW 1/4 SE 1/4 Sec 12 T 6 R 40 E Nye County  
 PERMIT NO. 12-411-05 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
<u>70% 3/8-1/2 gravel 30% med coarse sand</u>		<u>0</u>	<u>25</u>	<u>25</u>
<u>90% coarse med sand 10% clay</u>		<u>25</u>	<u>40</u>	<u>15</u>
<u>80% coarse sand 20% gravel black</u>		<u>40</u>	<u>80</u>	<u>40</u>
<u>50% coarse sand 50% gravel</u>		<u>80</u>	<u>180</u>	<u>50%</u>
<u>10% gravel 90% coarse silt rounded sand</u>	<input checked="" type="checkbox"/>	<u>130</u>	<u>140</u>	<u>10</u>
<u>10% gravel 90% coarse sand</u>	<input checked="" type="checkbox"/>	<u>140</u>	<u>160</u>	<u>20</u>
<u>90% coarse med sand 5% fine sand 5% gravel</u>	<input checked="" type="checkbox"/>	<u>160</u>	<u>200</u>	<u>40</u>

8. WELL CONSTRUCTION  
 Depth Drilled 200 Feet Depth Cased 200 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From 9 7/8 Inches To 0 Feet 200 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6.625</u>	<u>17.02</u>	<u>.250</u>	<u>+10"</u>	<u>20</u>
<u>6.625</u>	<u>5.006</u>	<u>.390</u>	<u>20</u>	<u>200</u>

(GDR17)

Perforations:  
 Type perforation Mill  
 Size perforation 48"  
 From 160 feet to 200 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 50  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Gravel Packed:  Yes  No  
 From 50 feet to 200 feet

9. WATER LEVEL  
 Static water level 95 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

Date started July 15, 2010  
 Date completed July 15, 2010

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>45</u>	<u>10</u>	<u>3:15</u>

7-15-10  
88:11:11 92:11:11  
2010 JUL 26 11:11:38  
RECEIVED

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Gardner Brothers Drilling Contractor  
 Address PO Box 965 Contractor  
Enterprise, UT 84725  
 Nevada contractor's license number issued by the State Contractor's Board 0068459  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 170  
 Signed Dale Gardner  
 By driller performing actual drilling on site or contractor  
 Date 7-22-10