

INS-22-4

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 111595
Permit No. -
Basin 087

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64221

1. OWNER Vista Campin Group
MAILING ADDRESS P.O. Box 281304, Lakewood, CO 80228

ADDRESS AT WELL LOCATION 255 S. Stanford Way Sparks NV 89431
Subdivision Name: County: Washoe

2. LOCATION SW, NW Sec 9, 19N, 20E
PERMIT/WAIVER No. NV-0020893 032-220-62
Issued by Water Resources Parcel No. RR16

Latitude 39° 31' 41" N UTM E NAD 27
Longitude 119° 44' 53" W N NAD 83/WGS 84

3. WORKED PERFORMED
 New Well Replace Recondition
 Deepen Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Silty Sand w/ cobbles		0	4	4
silt		4	5	1
Sandy gravel		5	28	23
Silty sand		28	31	3
Coarse sand w/gravel	X	31	50	19
12" Flush mount concrete		0	1.5	1.5
Bentonite chips		0	1.5	1.5
8/12 sand		1.5	46	44.5

9. WELL CONSTRUCTION

Depth Drilled	50	Feet	Depth Cased	50	Feet	
HOLE DIAMETER (BIT SIZE)						
	6"	Inches	0	Feet	50	Feet
		Inches		Feet		Feet
		Inches		Feet		Feet
CASING SCHEDULE						
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)		
2.5		Sch 80 PVC	.5	48		

Perforations:
Type of perforation Sch 80 S.S. Screen
Size of perforation 1.040 slot
From 48 feet to 50 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet
Annular Seal: Yes No
 Neat Cement to Pumped Poured
 Cement Grout to Pumped Poured
 Concrete Grout to Pumped Poured
 ≥30% Bentonite Grout to Pumped Poured
Gravel Pack: Yes No 46 to 50 Pumped Poured
Type: 8-12 Colorado Silica
Bentonite Chips: Yes No 1.5 to 46 Pumped Poured
Type: Wyoming

Date started: 7-23, 2010
Date completed: 7-23, 2010

7. Water Level
Static water level: 32 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name: Environmental West Exploration, Inc. Contractor
Address: P.O. Box 11095, Spokane, WA 99211 Contractor
Nevada contractor's license number issued by the State Contractor's Board: 0028363
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: 2832-temp 2387
Signed: [Signature] Driller performing actual drilling on-site or contractor
Date: July 30, 2010

8. WELL TEST DATA

TEST METHOD:	Bailer	Pump	Air Lift	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NAD-27 GPS 39.528144° N 119.747034° W						

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY