

IW-13

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 112240  
Permit No.  
Basin 44

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK  
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1 OWNER Yukon Nevada Gold Corp.  
MAILING ADDRESS HC 31 Box 78 ELKO, NV. 89801  
ADDRESS AT WELL LOCATION Territt Canyon Mine East DASH  
Subdivision Name: County:

2 LOCATION NW 1/4 NW 1/4 Sec 17 T 40 S R 54 E  
Latitude 412144.01636 UTM E 590079.19 NAD 27  
Longitude 1155522.95459 N 4579315.89 NAD 83/WGS 84  
Issued by Water Resources Parcel No.

3 Infection X TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled? NO  
If yes, what is replacement well NOI?  
Is there an existing well log? ~~no~~ yes  
If yes, what is NDWR well log #? 90763

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 1055 Feet Depth Cased 1050 Feet  
EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"	11.35	.25	0'	1050'

Existing Perforations:

Type of perforation	Size of perforation	From	To
Vert. Slot	8" x 2"	1050'	650'

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used: Air  
From 440' feet to 650' feet Number of perfs per linear foot 12

5 WATER LEVEL  
Static water level 558' feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature °F Quality

8 WELL PLUGGING MATERIALS

From	To	Material Used	Pumped	Poured
1050'	0'	Neat Cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments  
Rig up over IW-13 - Run 2 1/2" pipe down 4" casing to 1050'  
Clean well  
Trip out & put perforator on enter 4" casing & perforate 440' to 650' Double Pass.  
Trip out & take off perforator.  
Run Trime in well to 1050' mix & pump Neat Cement in. Lifts with Grout Tub TD. to Surface.  
8 1/2 yards of Neat Cement.

Neat Cement Fluid Weight Thick lbs/gal  
Bentonite Grout % bentonite  
Date Started 9-24-10  
Date Completed 9-25-10

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Ward Weaver Rimrock Drilling Contractor  
Address 2305 Last Chance Rd. ELKO, NV. 89801 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 0030630  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1676  
Signed Ward Weaver By driller performing actual drilling on-site or contractor  
Date 10-16-10